

no.54 Cork linoleum (sealed)



cleaning system without treatment end of construction

object address customer

		room classification			n representative		
work	process: select one work stage from each	n number				_	
	7	recommendations			recommendations	recommendations	
\searrow	cleaning method	* chemical products	dosage	*	pad / brush / mop / cloth	machine / tool	comments
	dusting				Masslinn 2000		
1	damp mopping			S	Microsol cloth		
	acbebbia			S	Synthetic fur		
4	dry vacuum			V S	Dust roller nozzle	Twinvac	is a control
1	cleaning			V	Combi-nozzle	Monovac	if needed
	cleaning without maintenance care	product (if coating fol	lows)			Portavac	
		Ecofloor	0.5 - 1%		Microbrush-mop	Wetbox system	
2	wet mopping single step	V Reshine	1 - 2%		Microsmooth-mop	Socar / Drewell	
_	single step	· rtoormio	1 270	v s	Silkysmooth-mop	Wetcar / Drewell	
	e corubbor drying	Ecofloor	0.5 - 1%		Pad red	Duo- / Discomatic	
2	scrubber drying ;	V Reshine	1 - 2%	V 🔵	Pad blue	Sprinter / Drivematic	
	single step					·	
	wet scrubbing and ;;	Reshine	1 - 2%		Pad red	Monomatic I / LS	△ ∧
2	wet vacuuming wet vacuuming	Antiwax forte	0.5 - 1%	V 🔵	Pad blue	Watertank	heavily soiled
		Antiwax forte classic				Twinvac / Duovac	
	cleaning with maintenance care (fi			roduc		I	
•	wet mopping	Redur	3 - 4%		Microbrush-mop	Wetbox system	
3	single step	Remop	2 - 3%	., 0	Microsmooth-mop	Socar / Drewell	
		Dodus	2 40/	V S	Silkysmooth-mop	Wetcar / Drewell	
3	scrubber drying	Redur Remop	3 - 4% 2 - 3%		Pad red	Duo- / Discomatic Sprinter / Drivematic	
J	single step	Nemoh	2-3/0			Opiniter / Driventatio	
-	• aproviologning ITTT	Waxspray	100%		Pad red	Monomatic DS	
3	spray cleaning i	Polish	30%	P	HS-Polish pad beige	Spray unit	after polishing
	<u>∡∡11</u> full spray		· ·	P	HS-Polish pad white	' ', ' ' '	

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: e.g. spot removal and basic cleaning with protective treatment. When spray cleaning, you should change your pad often.

no.54 Cork linoleum (sealed)



	maintenance cleaning			object address				
work i	process: select one work stage fror	n each	number	room classif	ication	1	representative	
	3							
<u> </u>	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				SS	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
1	dry vacuum cleaning				> s >	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed
	cleaning without maintenance	9						
2	wet mopping single step		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	C F F	Pad red Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	
2	polishing, vacuum polishing				C O	US-Polish pad beige HS-Polish pad beige Microsol fibre pad	Monomatic US Suction ring Monomatic HS	after polishing
	cleaning with maintenance							
2	wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	scrubber drying single step		Redur Remop	1 - 4% 1 - 2%	C F F	Pad red Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	
2	spray cleaning partial / full spray	[F Waxspray Polish	100% 30%		Pad red HS-Polish pad beige	Monomatic DS Spray unit	after polishing

HS-Polish pad white

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





interim cleaning			object			date		
				a	ddress	<u> </u>	customer	
				room classif	ication	1	representative	
<u>wor</u> k	process: select one work stage from	om each	number					
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				SS	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed
	cleaning without maintenand	ce						
2	wet mopping two-step		Reshine V Antiwax forte	2 - 5% 2 - 5%		Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	
2	scrubber drying two-step		Reshine Polex V Antiwax forte	2 - 5% 2 - 4% 2 - 5%	C F		Duo- / Discomatic Sprinter / Drivematic	
	cleaning with maintenance							
2	spray cleaning full spray		F Waxspray Polish	100% 30%	P	Pad red HS-Polish pad beige	Monomatic DS Spray unit	after polishing

HS-Polish pad white

important: When spray cleaning, you should change your pad often.

For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

no.54 Cork linoleum (sealed)



basic cleaning			objectaddress			date customer	_			
				room classif	ication	n	representative			
work	work process: select one work stage from each number									
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Portavac Monovac	if needed		
2	dusting damp mopping				S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
3	chewing gum removal		Karpfrost Karpotek	100% 100%				if needed		
	cleaning without maintenanc	е								
4	wet scrubbing and wet vacuuming		C Relino C Antiwax forte classic G Antiwax forte	20 - 50% 30 - 50% 30 - 50%	С	Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled		
4	scrubber drying two-step		C Relino C Antiwax forte classic G Antiwax forte	20 - 50% 30 - 50% 30 - 50%		Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas		
4	spray cleaning full spray		C Antiwax forte C Antiwax forte classic	30 - 50% 30 - 50%	С	Pad blue Microsol fibre pad	Monomatic I / LS Spray unit Monomatic LS	after polishir	ng 🗾 🌍	
5	rinsing		pure water	100%		Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac		рН 7	
5	rinsing		pure water	100%		Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas	pH 7	

important: change pad often.

Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





protective treatment			object			date		
				a	ddress		customer	
				room classif	ication		representative	
wor	k process: select one work stage fro	m each	number				_	
	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed
2	dusting damp mopping				SS	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
	first protective treatment (wit	h the s	same product as in mair		aning			
3	spray cleaning full spray		Waxspray	100%	P O	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing
	coating							
3	waxing		Polish	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
4	dusting damp mopping				S	Masslinn 2000 Synthetic fur	Balit with pad sole Balit with velcro	if needed
	buffing wax treatment (only it	fneces	ssary)					
5	нь рolishing, vacuum	; ;			c O	HS-Polish pad beige HS-Polish pad white	Monomatic HS Suction ring	after polishing

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

When spray cleaning, you should change your pad often.

Let dry protection treatment completely between the layers and before use.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

Monomatic DS

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no.54 Cork linoleum (sealed)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong alkalines can destroy or discolour cork linoleum coverings. Use a special basic linoleum cleaner! Cork linoleum coverings are sensitive to abrasive pads and brushes.

Cork linoleum coverings are largely insensitive to acids, fats, oils and solvents.

Certain manufacturers give cork linoleum coverings a surface finish at the factory (first maintenance).



Cork linoleum is a 100% natural product consisting of linseed oil, wood and cork granulates, resins, colorants and limestone on a jute underlay. Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: needle penetrates, typical smell, crater can be removed with the fingers.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.