

General instructions for cleaning and care



















no.9 PVC with electrostatic properties (conductive/antistatic)

cleaning system without treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting  damp mopping <input type="checkbox"/>			S Masslinn 2000 Microsol cloth	Balit with pad sole	
1  dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac	if needed
cleaning without maintenance care product (if coating follows)					
2   wet mopping single step <input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2  scrubber drying single step <input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	V  Pad red  Pad blue  Melamine pad	Duo- / Discomatic Sprinter / Drivematic	
2   wet scrubbing and wet vacuuming <input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	V  Pad blue  Pad green	Monomatic LS Watertank Twinvac / Duovac	heavily soiled  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Do not use magnetic tools and machines in the MRI and server room.

General instructions for cleaning and care

no.9 PVC with electrostatic properties (conductive/antistatic)










maintenance cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping	<input type="checkbox"/>			S Masslinn 2000 Microsol cloth	Balit with pad sole	
1  dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac	if needed
cleaning without maintenance						
2  wet mopping single step	<input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	if needed 
2  spray mopping (wet mopping)	<input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	if needed 
2  scrubber drying single step	<input type="checkbox"/>	B Granufloor Libero F Ecofloor	1 St/ 20l 1% 0.5 - 1%	● Pad red ● Melamine pad	Duo- / Discomatic Sprinter / Drivematic	if needed

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Do not use magnetic tools and machines in the MRI and server room.

Wet wipe only when necessary, if treated with Mepol Ohm, .

General instructions for cleaning and care

no.9 PVC with electrostatic properties (conductive/antistatic)













interim cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S Masslinn 2000 Microsol cloth	Balit with pad sole	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac	if needed
cleaning without maintenance							
2	 wet mopping two-step	<input type="checkbox"/>	Granufloor Libero	1St/10l 1%	V S Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	if needed  
2	 scrubber drying two-step	<input type="checkbox"/>	Granufloor Libero	1St/10l 1%	V  Pad red  Pad blue	Duo- / Discomatic Sprinter / Drivematic	if needed  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Do not use magnetic tools and machines in the MRI and server room.

General instructions for cleaning and care

no.9 PVC with electrostatic properties (conductive/antistatic)


































basic cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping	<input type="checkbox"/>			S Masslinn 2000 Microsol cloth	Balit with pad sole	
1  dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac	if needed
2  chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed 
cleaning without maintenance						
3   wet scrubbing and wet vacuuming	<input type="checkbox"/>	Antiwax forte classic 30 - 50% Speedclean 30 - 50% Remat 10 - 20%		V  Pad green  Pad black	Monomatic I / LS Wassertank Twinvac / Duovac	  
3  scrubber drying two-step	<input type="checkbox"/>	Antiwax forte classic 30 - 50% Speedclean 50% Remat 10 - 20%		V  Pad green  Pad black	Duo- / Discomatic Sprinter / Drivematic	large areas   
3  spray cleaning full spray	<input type="checkbox"/>	Antiwax forte classic 30 - 50% Speedclean 50.0% Remat 10 - 20%		 Pad green	Monomatic I / LS Spray unit	
4   rinsing	<input type="checkbox"/>	Klares Wasser	100%	 Microsol fibre pad  Pad green	Monomatic I / LS Twinvac / Duovac	 
4  rinsing	<input type="checkbox"/>	Klares Wasser	100%	 Microsol fibre pad  Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Do not use magnetic tools and machines in the MRI and server room.
 For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care



no.9 PVC with electrostatic properties (conductive/antistatic)

protective treatment

object _____

date _____






address _____

customer _____

room classification _____

representative _____

work process: select one work stage from each number

cleaning method		* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting  damp mopping			S Masslinn 2000 S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
coating						
2	 coating	Mepol Ohm	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	2-3 thin layers, let dry for at least 1 hour each.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Process treatment of protection: see description of method.

General instructions for cleaning and care



no.9 PVC with electrostatic properties (conductive/antistatic)

Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



PVC floor coverings are sensitive to certain solvents such as ketone, ester and chlorinated hydrocarbon.
Adequate humidity, i.e. at least 50% relative humidity, must be provided in rooms with floor coverings with electrostatic charges.


PVC floor coverings are sensitive to cigarette burns, glowing cigarettes and deposit marks.

PVC floor coverings are very resistant to strong alkalines and acids.

Fat-soluble colorants such as shoe polish or asphalt can penetrate into PVC floor coverings: diffusion.

The leakage resistance of antistatic floor coverings must be measured and recorded before and after basic cleaning.

It is recommended to check the leakage resistance approximately one week after maintenance cleaning.



PVC is a synthetic covering made from polyvinylchloride (PVC), softeners, fillers and colour pigments.

Homogeneous PVC floor coverings consist of one or more layers with the same composition.

Heterogeneous PVC floor coverings consist of several layers with the same basic materials but with a different composition.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: the needle penetrates, acrid smell, crater cannot be removed with fingers.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.