no. 25 Ceramic tiles, sintered, fine stone material



cleaning system without treatment end of construction

object address room classification

date _____ customer _____ esentative _____ representative

date

work process: select one work stage from each number

$\overline{\mathbf{V}}$	cleaning method	recommendations * chemical products dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments					
1	dusting damp mopping		Masslinn 2000 S Microsol cloth	Balit with pad sole						
1	dry vacuum cleaning		V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	if needed					
1	vacuum sweeping		V	Speedmatic Twister Master Sweep Turbo Sweep	large areas					
cleaning without maintenance										
2	wet mopping single step	Ecofloor 0.5 - 1% Ceratop 0.5 - 1% V Antiwax forte classic 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell						
2	scrubber drying single step	Ecofloor 0.5 - 1% Ceratop 0.5 - 1% V Antiwax forte classic 0.5 - 1%	 Microsol fibre pad S O Scrubbing brush Filament V O Melamine pad 	Duo- / Discomatic Sprinter / Drivematic						
2	wet scrubbing and wet vacuuming	V Reshine 1 - 2% V Antiwax forte classic 0.5 - 1%	S O Scrubbing brush Filament V O Melamine pad	Monomatic LS Watertank Twinvac / Duovac	heavily soiled					
3	stain removal	See cleaning instruction no 42			if needed					

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: green and black pad on hard stone only !

no. 25 Ceramic tiles, sintered, fine stone material



maintenance cleaning			a	object ddress		date					
work process: select one work stage fro	room classif			representative							
cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments				
1 dusting damp mopping	, 			S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro					
1 dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	if needed				
1 vacuum sweeping	g,			V		Speedmatic Twister Master Sweep Turbo Sweep	large areas				
cleaning without maintenance											
2 wet mopping single step	,, , , , , , , , , , , , , , , , , ,	Ecofloor Ceratop Biosan	0.5 - 1% 0.5 - 1% 0.8 - 1.5%	v	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell					
2 spray mopping (wet mopping)		Ecofloor Ceratop Biosan	0.5 - 1% 0.5 - 1% 0.8 - 1.5%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole					
2 scrubber drying single step		Ecofloor Ceratop Libero	0.5 - 1% 0.5 - 1% 0.5 - 3%	s () v ()	Microsol fibre pad Scrubbing brush Filament Melamine pad	Duo- / Discomatic Sprinter / Drivematic					
foam cleaning		See cleaning instruct	ion no 43								
cleaning with maintenance				- T		-	-				
2 wet mopping single step	,, , , , , , , , , , , , , , , , , ,	Redur Remop	1 - 4% 1 - 2%	v	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell					
2 scrubber drying single step		Ecofloor Ceratop Libero	0.5 - 1% 0.5 - 1% 0 5 - 3%	s © v ©	Microsol fibre pad Scrubbing brush Filament Melamine pad	Duo- / Discomatic Sprinter / Drivematic					

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

no. 25 Ceramic tiles, sintered, fine stone material



interim cleaning			object		date		_			
				a	ddress	i	customer			
work process: select one work stage from each number				room classification			representative			
Ţ	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping	,, , , , , , , , , , , ,			S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
1	dry vacuum cleaning	,, , , , , , , , ,			V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	if needed		
cleaning without maintenance										
2	wet mopping two-step	,, 	Reshine V Antiwax forte classic V Indumat	2 - 5% 2 - 5% 2 - 5%	v s	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell			
2	scrubber drying two-step		Reshine V Antiwax forte classic V Indumat	2 - 5% 2 - 5% 2 - 5%	s © v ©	0	Duo- / Discomatic Sprinter / Drivematic	green and black pad on hard stone only !		
	foam cleaning	,, , , , , , , , , , , , , , , , , ,	See cleaning instructi	on no 43						
3	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with		

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: green and black pad on hard stone only !

no. 25 Ceramic tiles, sintered, fine stone material



basic cleaning					object	t	date		_			
				a	ddress		customer	-				
work process: select one work stage from each number room class					ication	l	representative					
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments				
1	dusting damp mopping	, 			S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro					
1	dry vacuum cleaning	, 			VS V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	if needed				
2	chewing gum removal	, , 	Karpfrost Karpotek	100.0% 100.0%				if needed				
	cleaning without maintenance											
3	wet scrubbing and wet vacuuming	[]	Antiwax forte classic Remat	2 30 - 50% 10 - 20%	s () V ()	Microsol fibre pad Scrubbing brush Filament Pad green	Monomatic I / LS Watertank Twinvac / Duovac	green and black pad on hard stone only !				
3	scrubber drying two-step	,, , , , , , , , , ,	Antiwax forte classic Remat	2 30 - 50% 10 - 20%	s © v ●	Microsol fibre pad Scrubbing brush Filament Pad green	Duo- / Discomatic Sprinter / Drivematic	green and black pad on hard stone only !				
	foam cleaning	·,	See cleaning instruction	on no 43								
4	rinsing	, , 	0	100%	s 00	Scrubbing brush Supernylon	Monomatic I / LS Watertank Twinvac / Duovac		рн 7			
4	rinsing	, 	0	100%	s 00 s 0		Duo- / Discomatic Sprinter / Drivematic	large areas	рн 7			
5	stain removal	,, , , , , , , , , , , , , , , , , ,	See cleaning instruction				 	if needed				
6	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with				

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

no. 25 Ceramic tiles, sintered, fine stone material



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

Ceramic floor coverings are generally acid resistant. Sensitive or resistant against acid means against amidosulphuric acid. Sintered ceramic tiles are relatively insensitive to abrasive pads and brushes. Do not use wipe and care cleaners in wet rooms and hygiene rooms. Do not use maintenance products on sintered tiles. Do not use wipe and care cleaners on sintered ceramic tiles.

Ceramic floor coverings are heterogeneous products made from clay and aggregates such as feldspar and fluorite. The higher the firing temperature and the longer the time spent in the oven, the denser and more strongly sintered the ceramic will be. Earthenware: high water absorption (approx. 1,000°C), glazed earthenware: low water absorption (1,300°C). Slip resistance in commercial areas: classification R9 - R13 (low to very high) and V4 - V10, in bare foot areas A,B,C.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us. For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.