

General instructions for cleaning and care



no 27 Synthetic stone, polished, paving stones and Terrazzo

cleaning system with treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓ cleaning method		* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping			S Masslinn 2000 Microsol cloth Multi squeegee	Balit with pad sole	
1	dry vacuum cleaning			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	if needed
cleaning without maintenance care product (if coating follows)						
2	wet mopping single step	V Ecofloor V Reshine V Antiwax forte	0.5 - 1% 1 - 2% 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2	scrubber drying single step	V Ecofloor V Reshine V Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	Microsol fibre pad Pad blue V Pad green	Duo- / Discomatic Drivematic / Robomatic	green and black pad on hard stone only !
2	wet scrubbing and wet vacuuming	V Reshine V Antiwax forte classic	1 - 2% 0.5 - 1%	Microsol fibre pad Pad blue V Pad green	Monomatic LS Watertank Twinvac / Duovac	heavily soiled
3	stain removal	See cleaning instruction no 42				if needed
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)						
4	wet mopping single step	F Redur Remop Brill	3 - 4% 2 - 3% 3 - 5%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop
4	scrubber drying single step	F Redur Remop Brill	3 - 4% 2 - 3% 3 - 5%	Microsol fibre pad Pad red	Duo- / Discomatic Drivematic / Robomatic	
4	spray cleaning full spray	P Polyspray Elfspray	100% 100%	Pad red P HS-Polish pad beige P HS-Polish pad white	Monomatic DS Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care



no 27 Synthetic stone, polished, paving stones and Terrazzo

maintenance cleaning

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

	↓ cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				Masslinn S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	
cleaning without maintenance							
2	wet mopping single step		Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V Micro nonwoven-1 Micro woven-1 Silkysmooth-1	Variwet Plus Balit with velcro Micro velcro sole	
2	scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Drivematic / Robomatic	
2	HS polishing, vacuum polishing				B HS-Polish pad beige B HS-Polish pad white	Monomatic HS Suction unit Suction ring	after polishing
cleaning with maintenance							
2	wet mopping single step		Redur Remop Brill	1 - 4% 1 - 2% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	Brill should be used with Silkysmooth mop
2	scrubber drying single step		Redur Remop Brill	1 - 4% 1 - 2% 1 - 2%	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Drivematic / Robomatic	
2	spray cleaning partial / full spray		Polyspray Elfspray Polish	100% 100% 30%	Pad red P HS-Polish pad beige P HS-Polish pad white	Monomatic DS Spray unit	after polishing
2	US spray cleaning full spray		B US Restorer	100%	B US-Polish pad beige	Monomatic US Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care



no 27 Synthetic stone, polished, paving stones and Terrazzo

interim cleaning

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

	↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1		dusting damp mopping	<input type="checkbox"/>			F Masslinn 2000 B Masslinn B S Synthetic fur	Balit with pad sole Balit with velcro	
1		dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac Portavac	if needed
cleaning without maintenance								
2		wet mopping two-step	<input type="checkbox"/>	Reshine G Antiwax forte classic	2 - 5% 2 - 5%	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	
2		scrubber drying two-step	<input type="checkbox"/>	Reshine G Antiwax forte classic	2 - 5% 2 - 5%	Microsol fibre pad Pad red V Pad blue	Duo- / Discomatic Drivematic / Robomatic	
2		wet mopping single step	<input type="checkbox"/>	Biosan	3%	V S Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetbox system	if needed, bad smell could be removed with
cleaning with maintenance								
3		spray cleaning full spray	<input type="checkbox"/>	Polyspray Elfspray Polish	100% 100% 30%	Pad red P HS-Polish pad beige P HS-Polish pad white	Monomatic DS Spray unit	after polishing
3		US spray cleaning full spray	<input type="checkbox"/>	B US Restorer	100%	B US-Polish pad beige	Monomatic US Spray unit	after polishing

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care








































no 27 Synthetic stone, polished, paving stones and Terrazzo

basic cleaning

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓ cleaning method			recommendations	dosage	* recommendations	pad / brush / mop / cloth	recommendations	machine / tool	comments
* chemical products									
1		dusting damp mopping			B F B S	Masslinn Masslinn 2000 Synthetic fur	Balit with pad sole Balit with velcro		
1		dry vacuum cleaning			V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac		if needed
2		chewing gum removal		Karpfrost Karpotek	100% 100%				if needed 
cleaning without maintenance									
3		wet scrubbing and wet vacuuming		B Remat forte B Relino Antiwx forte classic	10 - 20% 20 - 50% 30 - 50%	 Microsol fibre pad B  Pad green	Monomatic I / LS Watertank Twinvac / Duovac		  
3		scrubber drying two-step		B Remat B Relino Antiwx forte classic	10 - 20% 20 - 50% 30 - 50%	 Microsol fibre pad B  Pad green	Duo- / Discomatic Drivematic / Robomatic	large areas	  
4		rinsing		pure water	100%	 Microsol fibre pad  Pad blue	Monomatic I / LS Watertank Twinvac / Duovac		 
4		rinsing		pure water	100%	 Microsol fibre pad  Pad blue	Duo- / Discomatic Drivematic / Robomatic	large areas	 
5		wet mopping single step		Biosan	3%	Silkysmooth-mop Microsmooth-mop Micro nonwoven-1	Wetbox system Wetcar / Drewell Variwet Plus	if needed, bad smell could be removed with	 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

important: green and black pad on hard stone only !
For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care

























no 27 Synthetic stone, polished, paving stones and Terrazzo

protective treatment

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓	cleaning method		recommendations * chemical products dosage		recommendations * pad / brush / mop / cloth		recommendations machine / tool	comments
1		dusting damp mopping			Masslinn 2000 S Microsol cloth S Synthetic fur		Balit with pad sole Balit with velcro	
pore filling (only if necessary)								
2		pore filling		Porosol	100%	Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.  
coating								
3		coating		Stoner Mepol HM	100% 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
3		waxing		Polish	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
buffing wax treatment (only if necessary)								
4		dusting damp mopping			Masslinn 2000		Balit with pad sole	if needed
4		polishing, vacuum polishing			C ○ HS-Polish pad white		Monomatic HS Suction unit Suction ring	after polishing 
coating								
2		impregnation		Imprasol	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	If necessary, one layer on porous surface. 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
do not coat impregnated floors.
Process treatment of protection: see description of method.
For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care




no 27 Synthetic stone, polished, paving stones and Terrazzo

Information about the flooring



Wetrot AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrot.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrot.com.
The recommended colours of pad and brushes consist to the actual wWetrot product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong acids can destroy cement-bound synthetic stone.
Cement-bound synthetic stone is sensitive to solvents.
Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!
There must be no coating in the open air and in wet rooms. Danger of slipping!



Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.
Cast stone is laid as finished slabs and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrot Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrot Academy, tel. +41 (0)43 255 51 43 or academy@wetrot.ch.