



cleaning system with treatment end of construction

customer
resentative
p

work process: select one work stage from each number

work	work process: select one work stage from each number								
Y F			recommendations			recommendations	recommendations		
	cleaning method		* chemical products	dosage	*	pad / brush / mop / cloth	machine / tool	comments	
1	dusting damp mopping					Masslinn 2000	Balit with pad sole		
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	if needed	
	cleaning without maintenance	e care	product (if coating follo	ows)					
2	wet mopping single step		V Reshine	0.5 - 1% 1 - 2%	v s	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetcar / Drewell Socar / Drewell Wetcar / Drewell		
2	scrubber drying single step		V Reshine	0.5 - 1% 1 - 2%	v	Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic		
2	wet scrubbing and wet vacuuming	[]	Reshine Antiwax forte Antiwax forte classic	1 - 2% 0.5 - 1% 0.5 - 1%		Pad blue	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled	
	cleaning with maintenance ca	are (fir	st protective treatment	with same p	roduc	t as in maintenance cleaning			
3	wet mopping single step		Redur Remop	3 - 4% 2 - 3%	v s	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell		
3	scrubber drying single step		Redur Remop	3 - 4% 2 - 3%		Pad red	Duo- / Discomatic Sprinter / Drivematic		
3	spray cleaning full spray		Polyspray Elfspray	100% 100%	P C	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing	

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: e.g. spot removal and basic cleaning with protective treatment. When spray cleaning, you should change your pad often.





maintenance cleaning				a	object ddress		date customer	
work	process: select one work stage fro	m each	number	room classif	ication		representative	
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				<i>S S</i>	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	if needed
	cleaning without maintenanc	е						
2	wet mopping single step		Ecofloor Reshine F Alcosal	0.5 - 1% 1 - 2% 1 - 2%	v s	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Ecofloor Reshine F Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	A
2	scrubber drying single step		Ecofloor Libero Reshine	0.5 - 1% 0.5 - 3% 1 - 2%	B O	Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic	
	cleaning with maintenance							
2	wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)	[]	Redur Remop	1 - 4% 1 - 2%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	scrubber drying single step		Redur Remop	1 - 4% 1 - 2%	B O	. aa biac	Duo- / Discomatic Sprinter / Drivematic	
2	spray cleaning partial / full spray		Polyspray Elfspray	100% 100%	P O	Pad red	Monomatic DS Spray unit	after polishing

important: When spray cleaning, you should change your pad often.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





interim cleaning					objec	t	date	
				a	ddress	S	customer	
				room classif	icatior	1	representative	
wor	k process: select one work stage fror	n each	number				_	
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed
	cleaning without maintenance)						
2	wet mopping two-step		Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	v s	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	
2	scrubber drying two-step		Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	B V F	Pad red Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	
2	polishing, vacuum polishing				B C F C	US-Polish pad beige HS-Polish pad white Microsol fibre pad	Monomatic US Suction ring Monomatic HS	after polishing
	cleaning with maintenance							
2	spray cleaning partial / full spray		Polyspray Elfspray	100% 100%	P C	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing
2	US spray cleaning		B US Restorer	100%	P) US-Polish pad beige) US-Polish pad beige	Monomatic US Spray unit	after polishing

important: When spray cleaning, you should change your pad often.

For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





	basic cleaning			a	object ddress		_ date customer		
wor	k process: select one work stage fror	m each	number	room classif			representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning	[]			V S V	Dust roller nozzle Combi-nozzle	Twinvac Portavac Monovac	if needed	
2	dusting damp mopping				S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro		
3	chewing gum removal		Karpfrost Karpotek	100% 100%				if needed	
	cleaning without maintenance	е							
4	scrubber drying single step		B Speedclean	50%	В	Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas	
4	wet scrubbing and wet vacuuming		B Speedclean B Relino C Antiwax forte	50% 20 - 50% 30 - 50%	B C S	Pad green Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	8	
4	scrubber drying single step		B Speedclean B Relino C Antiwax forte	50% 20 - 50% 30 - 50%	B C S	Pad green Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas	
4	spray cleaning full spray		C Antiwax forte C Antiwax forte classic	30 - 50% 30 - 50%	B C	Pad green Pad blue	Monomatic I / LS Spray unit Monomatic LS		
5	rinsing	[]	Klares Wasser	100%		Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac		pH 7
5	rinsing	[]	Klares Wasser	100%		Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas	рН 7

important: When white abrasion occurs, carry out a full clean to remove all the protective coating.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





	protective treatment				object		date		_	
				ac	ldress		customer		_	
				room classifi	cation		representative			
work	c process: select one work stage from	om each	number				_			
	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping				S S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
	pore filling (only if necessary	y)								
2	pore filling		F Porosol	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	If necessary, one layer on porous surface.		<u>F</u>
3	dry sanding					Pad blue Pad green	Monomatic I / LS Suction ring 0			
4	dusting damp mapping	[]			S	Masslinn 2000 Microsol cloth	Balit with pad sole Balit with velcro			

S Synthetic fur

important: if needed

For a few years now, linoleum coverings have often been provided with a PU protective layer at the factory.

No further protective treatment is usually required on this PU protective layer.

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





	protective treatment				object		date	
work	process: select one work stage from	n each	number	room classif	ddress ication		customer representative	
	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
5	dusting damp mopping				S S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with pad sole	
	coating							
6	coating		Mepol H Mepol HM Stoner	100% 100% 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
6	waxing		Polish	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
7	dry sanding					Pad blue	Monomatic LS Suction ring 0	fine sanding (if necessary)
8	dusting damp mopping	[]			В	Masslinn 2000 Synthetic fur	Balit with pad sole Balit with velcro	
9	coating		B Mepol H B Mepol HM B Stoner	100% 100% 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
9	waxing		C Polish	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
	buffing wax treatment (only if	neces	ssary)					
10	нз ј polishing, vacuum polishing				c 8	HS-Polish pad beige HS-Polish pad white	Monomatic HS Suction ring Monomatic DS	after polishing

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

APA 58 26.01.2022

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no.58 Linoleum (smooth)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong alkalines can destroy or discolour linoleum coverings. Use a special basic linoleum cleaner! Linoleum coverings are sensitive to abrasive pads and brushes.

Linoleum coverings are largely insensitive to acids, fats, oils and solvents.

Certain manufacturers give linoleum coverings a surface finish at the factory (first maintenance).



Linoleum is a 100% natural product consisting of linseed oil, wood and cork flour, resins, colorants and limestone on a jute underlay. Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: crater can be removed with the fingers.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.