

no. 40 Cement surface layer (rough)



cleaning system without treatment end of construction

object		date
address	C	ustomer
room classification	repres	entative

work process; select one work stage from each number

work	work process: select one work stage from each number							
] [recommendations			recommendations	recommendations	
\vee	cleaning method		* chemical products	dosage	*	pad / brush / mop / cloth	machine / tool	comments
	dry vacuum	11			V S	Dust roller nozzle	Twinvac	
1	cleaning	1 1			V	Combi-nozzle	Duovac	
	oleaning	<u>'</u>					Portavac	
	vacuum sweeping	,,			٧	Carpet set - Twister	Speedmatic Twister	large
1	sweeping	1 }					Master Sweep	areas
	Sweeping	<u></u> '					Turbo Sweep	aleas
	dusting	ı <u>!</u>			В	Masslinn 2000	Balit with pad sole	
1	damp mopping	-			S	Microsol cloth		if needed
	damp mopping	<u> </u>			۷В	Multi squeegee		
	cleaning without maintenance	e care	product (if coating follo	ows)				
	wet mopping	,,	Ecofloor	0.5 - 1%		Silkysmooth-mop	Socar / Drewell	^
2	single step		V Indumat	0.5 - 1%		Microsmooth-mop	Wetcar / Drewell	
	single step		V Antiwax forte classic	0.5 - 1%		Microbrush-mop	Wetbox system	
	scrubber drying		Ecofloor	0.5 - 1%		Microsol fibre pad	Duo- / Discomatic	
2	single step		V Reshine	1 - 2%		Pad blue	Sprinter / Drivematic	
	single step		V Antiwax forte classic	0.5 - 1%	s ©	Scrubbing brush Filament		
	wet scrubbing and	d ''	Ecofloor	0.5 - 1%		Microsol fibre pad	Monomatic LS	
2	wet vacuuming		Antiwax forte classic	0.5 - 1%		Pad blue	Watertank	heavily soiled
		<u> </u>	Reshine	1 - 2%	s ©		Twinvac / Duovac	
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)								
	wet mopping	11	Redur	3 - 4%		Silkysmooth-mop	Socar / Drewell	^
3	single step	į į	Remop	2 - 3%		Microsmooth-mop	Wetcar / Drewell	
	Single step					Microbrush-mop	Wetbox system	
	scrubber drying	,1	Redur	3 - 4%		Microsol fibre pad	Duo- / Discomatic	
3	single step		Remop	2 - 3%		Pad blue	Sprinter / Drivematic	
	3iiigic stop				S (©	Scrubbing brush Filament		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

no. 40 Cement surface layer (rough)



	maintenance cleaning				object		_ date	
				a	ddress		_ customer	
vork	process: select one work stage fro	m each	number	room classif	ication		representative	
Ţ	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	
1	vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
1	dusting damp mopping				B BS BS	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed
	cleaning without maintenance	e						
2	wet mopping single step		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%		Microbrush-mop Micro woven-1- Micro nonwoven-1-	Variwet handle Balit with velcro Micro velcro sole	
2	scrubber drying single step	[]	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%		Microsol fibre pad Pad red Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	
	cleaning with maintenance							
2	wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2	spray mopping (wet mopping)		Redur Remop	1 - 4% 1 - 2%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	scrubber drying single step		Redur Remop	1 - 4% 1 - 2%	SO	Microsol fibre pad Pad red	Duo- / Discomatic Sprinter / Drivematic	

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no. 40 Cement surface layer (rough)



	interim cleaning				object		date		<u></u>
work	process: select one work stage from	n each	number	room classif	ddress ication		customer representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				F S F	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac		
1	vacuum sweeping sweeping				>	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas	
1	dusting damp mopping	[]			B S S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed	
	cleaning without maintenance)							
2	wet mopping two-step		Reshine G Rewit 2000	2 - 5% 2 - 5%	v s	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell		
2	scrubber drying two-step		Reshine G Rewit 2000	2 - 5% 2 - 5%	S ©	Microsol fibre pad Pad blue Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic		
3	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro woven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with	

important: For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

no. 40 Cement surface layer (rough)



basic cleaning					object	t	_ date		_
				ac	ddress	8	customer		
wor	k process: select one work stage fror	n each	number	room classifi	cation	1	representative		
		freq	recommendations	5		recommendations	recommendations		
<u> </u>	cleaning method	uenc	* chemical product	s dosage	*	pad / brush / mop / cloth	machine / tool	comments	
1	dry vacuum cleaning				F S F	Dust roller nozzle Combi-nozzle	Monovac Portavac		
	oloaig						Twinvac		
1	vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas	
1	dusting damp mopping				B S B S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed	
2	chewing gum removal	[]	Karpotek Karpfrost	100% 100%			Monovac Portavac Twinvac	if needed	
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming	[]	Antiwax forte class G Rewit 2000 B Relino	10 - 20% 20 - 50%	©© — в	Scrubbing brush Filament Scrubbing brush washbeton Pad green	Monomatic I / LS Watertank Twinvac / Duovac		
3	scrubber drying two-step		Antiwax forte class G Rewit 2000 B Relino	10 - 20% 20 - 50%		Scrubbing brush Filament Scrubbing brush Tynex Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas	
4	rinsing	[]	0	100%	S S	Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Monomatic I / LS Watertank Twinvac / Duovac		pH 7
4	rinsing		0	100%	⊘ (⊙(⊙) ∽		Duo- / Discomatic Sprinter / Drivematic	large areas	pH 7
5	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro woven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with	

important: change pad often.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no.40 Cement surface layer (rough)



	protective treatment				object ddress		date customer	<u></u>	
work process: select one work stage from each number			number	room classification			representative		
1	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				F S F	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac		
1	dusting damp mopping				S B S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed	
	pore filling (only if necessary	y)							
2	pore filling		F Porosol	100%		Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.	
	coating								
3	coating		Stoner Mepol HM	100% 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers	
4	dusting damp mopping				B S B S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed	
	coating								
2	impregnation		F Imprasol	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.	

important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! do not coat impregnated floors.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no.40 Cement surface layer (rough)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Do not coat structured floor coverings.

Strong acids and abrasive pads and brushes can destroy limestone and cement-bonded artificial stone.

Cement floors are sensitive to strong acids and strongly alkaline cleaners.

Do not use maintenance and protection products in wet areas. Danger of slipping!



Cement mortar consists of Portland cement and sand.

Cement coatings are painted with special concrete paints and treated with concrete sealants.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.