

# General instructions for cleaning and care

## no.21 Asphalt (smooth)
















cleaning system without treatment  
end of construction

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	
1  vacuum sweeping <input type="checkbox"/>			V	Speedmatic Twister Turbo Sweep	large areas
1  dusting damp mopping <input type="checkbox"/>			B S Masslinn 2000 F Microsol cloth F Synthetic fur	Balit with pad sole Balit with velcro	if needed
<b>cleaning without maintenance care product (if coating follows)</b>					
2  wet mopping single step <input type="checkbox"/>	Ecofloor Polex V Rewit 2000	0.5 - 1% 0.5 - 1% 0.5 - 1%	V S Microbrush-mop Microbrush-mop S Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2  scrubber drying single step <input type="checkbox"/>	Ecofloor Polex V Rewit 2000	0.5 - 1% 0.5 - 1% 0.5 - 1%	Microsol fibre pad Pad red	Duo- / Discomatic Sprinter / Drivematic	
2  scrubber drying single step <input type="checkbox"/>	Polex V Rewit 2000	0.5 - 1% 0.5 - 1%	V Microsol fibre pad Pad red Pad blue	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled  
3  stain removal <input type="checkbox"/>	See cleaning instruction no 42				if needed
<b>cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)</b>					
4  wet mopping single step <input type="checkbox"/>	F Redur Brill Remop	3 - 4% 3 - 5% 2 - 3%	V S Microbrush-mop Microbrush-mop S Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop only.
4  scrubber drying single step <input type="checkbox"/>	F Redur Brill Remop	3 - 4% 3 - 5% 2 - 3%	Microsol fibre pad Pad red	Duo- / Discomatic Sprinter / Drivematic	

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.21 Asphalt (smooth)




















### maintenance cleaning

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac Portavac	
1	 vacuum sweeping	<input type="checkbox"/>			V	Speedmatic Twister Turbo Sweep	large areas
1	 dusting damp mopping	<input type="checkbox"/>			B Masslinn B S Microsol cloth F Synthetic fur	Balit with pad sole Balit with velcro	
<b>cleaning without maintenance</b>							
2	 wet mopping single step	<input type="checkbox"/>	Ecofloor Polex Biosan	0.5 - 1% 0.5 - 1% 0.8 - 1.5%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	 spray mopping (wet mopping)	<input type="checkbox"/>	Ecofloor Polex	0.5 - 1% 0.5 - 1%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	 scrubber drying single step	<input type="checkbox"/>	Ecofloor Polex	0.5 - 1% 0.5 - 1%	B  Microsol fibre pad B  Pad red	Duo- / Discomatic Sprinter / Drivematic	
<b>cleaning with maintenance</b>							
2	 wet mopping single step	<input type="checkbox"/>	Redur Remop	1 - 4% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	 spray mopping (wet mopping)	<input type="checkbox"/>	Redur Remop	1 - 4% 1 - 2%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	 scrubber drying single step	<input type="checkbox"/>	Redur Brill Remop	1 - 4% 1 - 2% 1 - 2%	B  Microsol fibre pad B  Pad red	Duo- / Discomatic Sprinter / Drivematic	

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.21 Asphalt (smooth)

















### interim cleaning

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S V	<b>Dust roller nozzle</b> Combi-nozzle	<b>Monovac</b> Twinvac Portavac	
1	 vacuum sweeping	<input type="checkbox"/>			V	<b>Speedmatic Twister</b> Turbo Sweep	large areas	
1	 dusting damp mopping	<input type="checkbox"/>			B B S F	<b>Masslinn</b> Microsol cloth Synthetic fur	<b>Balit with pad sole</b> Balit with velcro	if needed
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b> 100%			if needed 	
<b>cleaning without maintenance</b>								
3	 wet mopping two-step	<input type="checkbox"/>	<b>Polex</b> Rewit 2000	<b>2 - 4%</b> 2 - 5%	V S	<b>Microsmooth-mop</b> Silkysmooth-mop	<b>Socar / Drewell</b> Wetcar / Drewell	 
4	 scrubber drying two-step	<input type="checkbox"/>	<b>Polex</b> Rewit 2000	<b>2 - 4%</b> 2 - 5%	B	 <b>Microsol fibre pad</b> Pad blue	<b>Duo- / Discomatic</b> Sprinter / Drivematic	 
5	 wet mopping single step	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>		<b>Silkysmooth-mop</b> Microbrush-mop Micro nonwoven-1-	<b>Wetbox system</b> Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with 

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

**important:** For initial cleaning after interim cleaning, see "initial cleaning".

# General instructions for cleaning and care

## no.21 Asphalt (smooth)
























### basic cleaning

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	freq uenc	recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning	<input type="checkbox"/>			V S V Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	
1  dusting damp mopping	<input type="checkbox"/>			B B S B S Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed
2  chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed 
<b>cleaning without maintenance</b>						
3  wet scrubbing and wet vacuuming	<input type="checkbox"/>	Rewit 2000	10 - 20%	● Pad blue B ● Pad green	Monomatic I / LS Watertank Twinvac / Duovac	attention: modification of surface   
3  scrubber drying two-step	<input type="checkbox"/>	Rewit 2000	10 - 20%	● Pad blue B ● Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas   
4  rinsing	<input type="checkbox"/>	pure water	100%	● Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	 
4  rinsing	<input type="checkbox"/>	pure water	100%	● Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas  
5  wet mopping single step	<input type="checkbox"/>	Biosan	3%	Silkysmooth-mop Microbrush-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

**important:** For initial cleaning after basic cleaning, see "initial cleaning".

# General instructions for cleaning and care

## no.21 Asphalt (smooth)




















### protective treatment

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	recommendations chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
 1  dry vacuum cleaning 			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Monovac</b> Twinvac Portavac	if needed
2  dusting damp mopping 			B <b>Masslinn 2000</b> B S Microsol cloth B S Synthetic fur	<b>Balit with pad sole</b> Balit with velcro	
<b>pore filling (only if necessary)</b>					
3  pore filling 	F <b>Porosol</b>	<b>100%</b>	<b>Cover for Florfix</b> Florfix-mop Multi squeegee	<b>Florfix</b> Balit with velcro	If necessary, one layer on porous surface.  
<b>coating</b>					
3  coating 	<b>Stoner</b>	<b>100%</b>	<b>Cover for Florfix</b> Florfix-mop	<b>Florfix</b> Balit with velcro	1 - 3 thin layers  
<b>coating</b>					
2  impregnation 	F <b>Imprasol</b>	<b>100%</b>	<b>Cover for Florfix</b> Florfix-mop	<b>Florfix</b> Balit with velcro	apply first layer with care.  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

### important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

do not coat impregnated floors.

Process treatment of protection: see description of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

## General instructions for cleaning and care

### no.21 Asphalt (smooth)



#### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrok.com](http://www.wetrok.com).  
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrok.com](http://www.wetrok.com).  
The recommended colours of pad and brushes consist to the actual wWetrok product range.  
Follow the special cleaning and care instructions of the floor manufacturer.  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



**Asphalt is sensitive to solvents, oils and fats. Do not use solvent-based cleaners or waxes!**  
**Asphalt coverings with mineral aggregates are acid-sensitive.**

Asphalt coverings are relatively insensitive to abrasive pads and brushes.  
Asphalt is temperature-sensitive and softens at temperatures above 60°C.  
Asphalt is sensitive to high pressure loads.



Asphalt is a blend of bitumen and minerals, such as chippings, sand and stone flour.  
Mastic asphalt is cast without joints, layer thickness 15 - 30mm.  
Compressed asphalt sheets are sheets compressed under high pressure and they often have acid-sensitive cement mortar.

Distinguishing feature: solution assay: apply a little solvent (e.g. alcohol) to the asphalt covering and wipe. Dark, porous stain: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.  
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.  
Test on an inconspicuous spot to find which product is suitable for your requirements.  
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.  
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.  
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or [academy@wetrok.ch](mailto:academy@wetrok.ch).

**Wetrok AG** Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, [info@wetrok.ch](mailto:info@wetrok.ch), [www.wetrok.com](http://www.wetrok.com).