

General instructions for cleaning and care

no.53 Wood or cork parquet (waxed)


























cleaning system with treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓	cleaning method	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping			Masslinn 2000	Balit with pad sole	
1	 dry vacuum cleaning			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	if needed
cleaning without maintenance care product (if coating follows)						
2	 wet mopping single step	F Antiwax forte classic F Reshine F Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Silkysmooth-mop Microsmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	 
2	 scrubber drying single step	F Antiwax forte classic F Reshine F Polex	0.5 - 1% 1 - 2% 0.5 - 1%	● Pad red V  Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	
2	 wet scrubbing and wet vacuuming	F Antiwax forte classic F Reshine F Polex	0.5 - 1% 1 - 2% 0.5 - 1%	● Pad red V  Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled   
2	 HS  polishing, vacuum polishing			C ● HS-Polish pad beige C ○ HS-Polish pad white	Monomatic HS Suction ring Suction unit	after polishing 
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)						
3	 wet mopping single step	F Brill F Redur F Remop	3 - 5% 3 - 4% 2 - 3%	Silkysmooth-mop Microsmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop only.  
3	 scrubber drying single step	F Brill F Redur F Remop	3 - 5% 3 - 4% 2 - 3%	● Pad red V ● Pad blue	Duo- / Discomatic Sprinter / Drivematic	
3	 spray cleaning full spray	Polyspray F Elfspray F Polish	100% 100% 30%	● Pad red P ● HS-Polish pad beige P ○ HS-Polish pad white	Monomatic DS Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.53 Wood or cork parquet (waxed)
































maintenance cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			V Masslinn Multi squeegee	Balit with pad sole	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Portovac Twinvac	if needed
cleaning without maintenance							
2	 wet mopping single step	<input type="checkbox"/>	Reshine Polex Alcosal	1 - 2% 0.5 - 1% 1 - 2%	Silkysmooth-mop Microsmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	if needed  
2	 spray mopping (wet mopping)	<input type="checkbox"/>	Reshine Polex Alcosal	1 - 2% 0.5 - 1% 1 - 2%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	 
2	 scrubber drying single step	<input type="checkbox"/>	Reshine Polex Libero	1 - 2% 0.5 - 1% 0.5 - 3%	V  Pad red V  Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	if needed 
2	 HS polishing, vacuum polishing	<input type="checkbox"/>			C  HS-Polish pad beige C  US-Polish pad beige C  Polishing brush Union	Monomatic HS Suction ring Monomatic US	after polishing 
cleaning with maintenance							
3	 wet mopping single step	<input type="checkbox"/>	Brill Redur Remop	1 - 2% 1 - 4% 1 - 2%	Silkysmooth-mop Microsmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	Brill should be used with Silkysmooth mop only.  
3	 scrubber drying single step	<input type="checkbox"/>	Brill Redur Remop	1 - 2% 1 - 4% 1 - 2%	V  Pad red V  Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	if needed 
3	 spray cleaning partial / full spray	<input type="checkbox"/>	Polyspray Elfspray Polish	100% 100% 30%	 Pad red P  HS-Polish pad beige P  HS-Polish pad white	Monomatic DS Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often.

General instructions for cleaning and care

no.53 Wood or cork parquet (waxed)




















interim cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth *	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S Masslinn Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Portavac Twinvac	if needed
cleaning without maintenance							
2	 wet mopping two-step	<input type="checkbox"/>	Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	Silkysmooth-mop Microsmooth-mop	Socar / Drewell Wetcar / Drewell	  
2	 scrubber drying two-step	<input type="checkbox"/>	Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	● Pad red V ● Pad blue V ● Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	  
cleaning with maintenance							
3	 spray cleaning full spray	<input type="checkbox"/>	Polyspray Elfspray Polish	100% 100% 30%	● Pad red P ● HS-Polish pad beige P ○ HS-Polish pad white	Monomatic DS Spray unit	after polishing 
3	 wet mopping single step	<input type="checkbox"/>	Polish	30%	Silkysmooth-mop Microsmooth-mop	Socar / Drewell Wetcar / Drewell	 
buffing wax treatment (only if necessary)							
4	 HS polishing, vacuum polishing	<input type="checkbox"/>			C ● HS-Polish pad beige C ○ HS-Polish pad white	Monomatic HS Suction ring Monomatic DS	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often.
 For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no. 53 Wood or cork parquet (waxed)



































basic cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V S V Dust roller nozzle Combi-nozzle	Twinvac Portovac Monovac	if needed
2	 dusting damp mopping	<input type="checkbox"/>			S S Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
3	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed 
cleaning without maintenance							
4	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	C Antiwax forte C Antiwax forte classic C Relino	30 - 50% 30 - 50% 20 - 50%	C  Pad green  Pad blue  Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled   
4	 scrubber drying two-step	<input type="checkbox"/>	C Antiwax forte C Antiwax forte classic C Relino	30 - 50% 30 - 50% 20 - 50%	C  Pad green  Pad blue  Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas   
4	 spray cleaning full spray	<input type="checkbox"/>	C Antiwax forte C Antiwax forte classic	30 - 50% 30 - 50%	C  Pad green  Pad blue	Monomatic DS Spray unit Monomatic LS	
5	 rinsing	<input type="checkbox"/>	pure water	100%	 Pad blue  Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	 pH 7 
5	 rinsing	<input type="checkbox"/>	pure water	100%	 Pad blue  Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas  pH 7 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: After basic cleaning, protective treatment is necessary!
 green pad on hard wood only !
 Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

General instructions for cleaning and care

no. 53 Wood or cork parquet (waxed)











protective treatment

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

cleaning method	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V S Combi-nozzle	Monovac Portavac Twinvac	if needed
2  dusting damp mopping <input type="checkbox"/>			Masslinn 2000 S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
coating					
3  waxing <input type="checkbox"/>	Polish	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
4  dusting damp mopping <input type="checkbox"/>			Masslinn 2000 S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	if needed
buffing wax treatment (only if necessary)					
5  polishing, vacuum polishing <input type="checkbox"/>			C ● HS-Polish pad beige C ○ HS-Polish pad white	Monomatic HS Suction ring Suction unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
 floor has to be grinded it change le system from the cired to oiled system.
 Let dry protection treatment completely between the layers and before use.
 Process treatment of protection: see descriptione of method.
 For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care

no. 53 Wood or cork parquet (waxed)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong alkalines can destroy or discolour wood coverings. Use a special basic linoleum cleaner!

Wood coverings are sensitive to abrasive pads and brushes.

Permanent exposure to moisture should be avoided with wood coverings. Mop as little as possible and wring out the mop thoroughly.
Allow it to dry completely before applying a protective treatment! Allow longer drying times than for non-porous coverings such as PVC.



Hardwoods (deciduous wood) such as oak, beech, ash, maple, walnut and acacia, or exotic woods, are processed into parquet.
Softwoods (coniferous wood) such as spruce, fir and pine are mostly used in the manufacturing of floor boards (long tongue-and-groove boards).
Humidity variations cause wood to shrink (dry out) or swell (exposure to moisture) and, possibly, warp (moisture).
Distinguishing feature: appearance of wood, dull sound when tapped.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.