# no.33 Natural stone, acid-susceptible (sanded)



cleaning system without treatment	object_	date	
end of construction	address	customer	
	room classification	representative	

work process: select one work stage from each number								
	cleaning method	recommendations * chemical products dosa		recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dry vacuum cleaning	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	V S V	<b>Dust roller nozzle</b> Combi-nozzle	Twinvac Monovac Portavac	if needed		
2	dusting damp mopping	1	B B S	Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro			
	cleaning without maintenance car							
3	wet mopping single step	L         Ecofloor         0.5 - 1           V         Reshine         1 - 2           V         Antiwax forte classic         0.5 - 1	% %	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell			
3	scrubber drying single step	Ecofloor	% V 🦣	<u> </u>	Duo- / Discomatic Sprinter / Drivematic			
3	wet scrubbing and wet vacuuming	Reshine 1 - 2 Antiwax forte classic 0.5 - 1		Microsol fibre pad Pad red	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled		
4	stain removal	See cleaning instruction no 42			 	if needed		
	cleaning with maintenance care (f							
5	wet mopping single step	Remop 2 - 3		Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell			
5	scrubber drying single step	Redur 3 - 4 Remop 2 - 3		Microsol fibre pad Pad red	<b>Duo- / Discomatic</b> Sprinter / Drivematic			
5	spray cleaning full spray	Polyspray 100 B Elfspray 100		Pad red  HS-Polish pad beige  HS-Polish pad white	Monomatic DS Spray unit	after polishing		

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# no. 33 Natural stone, acid-susceptible (sanded)



	maintenance cleaning				object ddress		_ date customer	
work	c process: select one work stage from	n each	number	room classif			representative	
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				B B S	Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro	Vacuum dry if necessary.
	cleaning without maintenance	•						
3	wet mopping single step		Ecofloor Reshine Alcosal	<b>0.5 - 1%</b> 1 - 2% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
3	spray mopping (wet mopping)		Ecofloor Reshine Alcosal	<b>0.5 - 1%</b> 1 - 2% 1 - 2%	V	Microbrush-mop Micro woven-1- Micro nonwoven-1-	Variwet handle Balit with velcro Micro velcro sole	
3	scrubber drying single step		Ecofloor Reshine Libero	<b>0.5 - 1%</b> 1 - 2% 0.5 - 3%	v <b>\</b>	Microsol fibre pad Pad red Melamine pad	Duo- / Discomatic Sprinter / Drivematic	
3	polishing, vacuum polishing				В () В () В ()	HS-Polish pad beige HS-Polish pad white US-Polish pad beige	Monomatic HS Suction ring Monoma Monomatic US	after polishing
	cleaning with maintenance							
3	wet mopping single step		<b>Redur</b> Remop	<b>1 - 4%</b> 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
3	scrubber drying single step		<b>Redur</b> Remop	<b>1 - 4%</b> 1 - 2%	>	Microsol fibre pad Pad red Melamine pad	<b>Duo- / Discomatic</b> Sprinter / Drivematic	
3	spray cleaning partial / full spray		Polyspray B Elfspray	<b>100%</b> 100%	P P	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing
3	US spray cleaning partial / full spray		B US Restorer	100%		US-Polish pad beige	Monomatic US Spray unit	after polishing

important: Sensitive or resistant against acid means against amidosulphuric acid.

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



# no.33 Natural stone, acid-susceptible (sanded)



interim cleaning			object			date			
work	nracean calcat and work stage fr	.m .a.a.h	numbar	address			customer		
WOIK	process: select one work stage fro	om each	number	room classif	ication	l <u> </u>	representative		
<u> </u>	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping	 			B B S	Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro		
1	dry vacuum cleaning	 			V S V	<b>Dust roller nozzle</b> Combi-nozzle	Monovac Portavac Twinvac	if needed	
	cleaning without maintenand	ce							
2	wet mopping two-step		Reshine G Rewit 2000	<b>2 - 5%</b> 2 - 5%	v s	<b>Microsmooth-mop</b> Silkysmooth-mop	Socar / Drewell Wetcar / Drewell		
2	scrubber drying two-step		Reshine G Rewit 2000	<b>2 - 5%</b> 2 - 5%	<b>&gt;</b>	Microsol fibre pad Pad red	<b>Duo- / Discomatic</b> Sprinter / Drivematic		
cleaning with maintenance									
2	spray cleaning full spray		Polyspray B Elfspray	<b>100%</b> 100%	P (	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing	
2	spray cleaning full spray		B US Restorer	100%		US-Polish pad beige	Monomatic US Spray unit	after polishing	

important: Sensitive or resistant against acid means against amidosulphuric acid.

When spray cleaning, you should change your pad often.

For initial cleaning after interim cleaning, see "initial cleaning".

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# no.33 Natural stone, acid-susceptible (sanded)



basic cleaning				object address			date customer		_
wor	k process: select one work stage fro	m each	number	room classif	fication		representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning	 			V S V	<b>Dust roller nozzle</b> Combi-nozzle	Twinvac Monovac Portavac	if needed	
2	dusting damp mopping				B B S	Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro		
3	chewing gum removal		<b>Karpfrost</b> Karpotek	<b>100%</b> 100%				if needed	
cleaning without maintenance									
4	wet scrubbing and wet vacuuming		Antiwax forte classic Antiwax forte	<b>c 30 - 50%</b> 30 - 50%	В	Microsol fibre pad Pad red Pad blue	Monomatic I / LS Watertank Twinvac / Duovac	<b>\Sigma</b>	
4	scrubber drying two-step		Antiwax forte classic Antiwax forte	<b>c 30 - 50%</b> 30 - 50%	В	Microsol fibre pad Pad red Pad blue	<b>Duo- / Discomatic</b> Sprinter / Drivematic	large areas	
5	rinsing		0	100%		Microsol fibre pad Pad red	Monomatic I / LS Watertank Twinvac / Duovac		рН 7
5	rinsing		0	100%		Microsol fibre pad Pad red	<b>Duo- / Discomatic</b> Sprinter / Drivematic	large areas	pH 7
6	stain removal	 	See cleaning instructi	ion no 42				if needed	
7	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with	

important: Sensitive or resistant against acid means against amidosulphuric acid.

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



## no.33 Natural stone, acid-susceptible (sanded)



	protective treatment				object dress		_ date customer		
wor	k process: select one work stage fro	om each	number	room classific			representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping				S	Masslinn 2000 Microsol cloth	Balit with pad sole		
	pore filling (only if necessary	y)							
2	pore filling		F Porosol	100%		Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.	
	coating								
3	coating	[]	Stoner	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers	
3	waxing		Polish	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers	
	coating								
3	impregnation		F Imprasol	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.	

### important: if needed

Sensitive or resistant against acid means against amidosulphuric acid.

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! do not coat impregnated floors.

Let dry protection treatment completely between the layers and before use.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

<sup>\*</sup> basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



## no.33 Natural stone, acid-susceptible (sanded)



### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofer stone, travertine, slate or sandstone is sensitive to acid.

Sensitive or resistant against acid means against amidosulphuric acid.

Soft stone is sensitive to scratches, only use suitable pads and brushes.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

Soak the joints well or saturate them with an alkali cleaning solution before removing cement residue or limescale.

There must be no coating in the open air and in wet rooms. Danger of slipping!

Fats and oils can penetrate into the stone covering. Stain formation!

Spray cleaning only for small joints and flat surfaces; no fillet joints.

Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Distinguishing feature: natural stone acid-proof acid assay: basic sanitary cleaner foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.