

General instructions for cleaning and care

no.28 Synthetic and natural stone, acid-susceptible (structured profile)















cleaning system without treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method	recommendation: * chemical product	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	large areas: sweeping
2  dusting damp mopping <input type="checkbox"/>			S Masslinn 2000 S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	if needed
cleaning without maintenance care product (if coating follows)					
3  wet mopping single step <input type="checkbox"/>	Ecofloor V Reshine V Antiwax forte class	0.5 - 1% 1 - 2% 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
3  scrubber drying single step <input type="checkbox"/>	Ecofloor V Reshine V Antiwax forte class	0.5 - 1% 1 - 2% 0.5 - 1%	Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	
3  wet scrubbing and wet vacuuming <input type="checkbox"/>	Reshine V Antiwax forte	1 - 2% 0.5 - 1%	Microsol fibre pad Scrubbing brush washbeton Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled  
4  stain removal <input type="checkbox"/>		See cleaning instruction no 42			if needed
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)					
5  wet mopping single step <input type="checkbox"/>	Redur Remop F Brill	3 - 4% 2 - 3% 3 - 5%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop only. 
5  scrubber drying single step <input type="checkbox"/>	Redur Remop F Brill	3 - 4% 2 - 3% 3 - 5%	Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care

no.28 Synthetic and natural stone, acid-susceptible (structured profile)



maintenance cleaning

object _____

date _____












address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendation: chemical product	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V S V Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	
1	 vacuum sweeping	<input type="checkbox"/>				Speedmatic Twister Master Sweep Turbo Sweep	large areas
2	 dusting damp mopping	<input type="checkbox"/>			S S Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	if needed
cleaning without maintenance							
3	 wet mopping single step	<input type="checkbox"/>	Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
3	 spray mopping (wet mopping)	<input type="checkbox"/>	Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
3	 scrubber drying single step	<input type="checkbox"/>	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	⊕ V ⊙ ⊙ Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	
cleaning with maintenance							
3	 wet mopping single step	<input type="checkbox"/>	F Redur Brill	1 - 4% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	Brill should be used with Silkysmooth mop only.
3	 scrubber drying single step	<input type="checkbox"/>	F Redur Brill	1 - 4% 1 - 2%	V ⊕ ⊙ ⊙ Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care

no. 28 Synthetic and natural stone, acid-susceptible (structured profile)



interim cleaning

object _____

date _____














address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendation: chemical product	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			V S V Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	
1	 vacuum sweeping	<input type="checkbox"/>				Speedmatic Twister Master Sweep Turbo Sweep	large areas
2	 dusting damp mopping	<input type="checkbox"/>			B B S Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro	if needed
cleaning without maintenance							
3	 wet mopping two-step	<input type="checkbox"/>	Reshine G Antiwax forte class	2 - 5% 2 - 5%	Microsmooth-mop Silkysmooth-mop Microbrush-mop	Socar / Drewell Wetcar / Drewell	 
3	 scrubber drying two-step	<input type="checkbox"/>	Reshine G Antiwax forte class	2 - 5% 2 - 5%	 Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	 
4	 wet mopping single step	<input type="checkbox"/>	Biosan	3%	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	if needed, bad smell could be removed with  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.
For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no.28 Synthetic and natural stone, acid-susceptible (structured profile)



basic cleaning

object _____

date _____























address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendation: chemical product dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>		V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	
2	 dusting damp mopping	<input type="checkbox"/>		B Masslinn 2000 B S Masslinn B S Synthetic fur	Balit mit Padsohle Balit with velcro	if needed
3	 chewing gum removal	<input type="checkbox"/>	Karpfrost 100% Karpotek 100%			if needed 
cleaning without maintenance						
4	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Antiwax forte clas 30 - 50% G Rewit 2000 10 - 20% B Relino 20 - 50%	Microsol fibre pad Scrubbing brush washbeton V Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	  
4	 scrubber drying two-step	<input type="checkbox"/>	Antiwax forte clas 30 - 50% G Rewit 2000 10 - 20% B Relino 20 - 50%	Microsol fibre pad V Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	large areas   
5	 rinsing	<input type="checkbox"/>	0 100%	Microsol fibre pad V Scrubbing brush Filament Scrubbing brush washbeton	Monomatic I / LS Watertank Twinvac / Duovac	 
5	 rinsing	<input type="checkbox"/>	0 100%	Microsol fibre pad V Scrubbing brush Filament Scrubbing brush washbeton	Duo- / Discomatic Sprinter / Drivematic	large areas  
6	 stain removal	<input type="checkbox"/>	See cleaning instruction no 42			if needed
7	 wet mopping single step	<input type="checkbox"/>	Biosan 3%	Silksmooth-mop Microsmooth-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care

no. 28 Synthetic and natural stone, acid-susceptible (structured profile)



protective treatment

object _____

date _____




















address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

cleaning method	recommendation: * chemical product dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting  damp mopping 		Masslinn 2000 Synthetic fur	Balit with pad sole Balit with velcro	
pore filling (only if necessary)				
2  pore filling 	F Porosol 100%	Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.  
coating				
3  coating 	Stoner Mepol HM 100% 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
3  waxing 	Polish 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
coating				
2  impregnation 	F Imprasol 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.
 before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
 do not coat impregnated floors.
 Process treatment of protection: see description of method.
 For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care

no. 28 Synthetic and natural stone, acid-susceptible (structured profile)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Do not coat structured floor coverings.

Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofen stone, travertine, slate or sandstone is sensitive to acid.

Sensitive or resistant against acid means against amidosulphuric acid.

Soft stone is sensitive to scratches, only use suitable pads and brushes.

Plastic-bonded synthetic stone is sensitive to solvents.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.



There must be no coating in the open air and in wet rooms. Danger of slipping!

Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.

Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Cast stone is laid as plates and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.