

# General instructions for cleaning and care

## no.42 Removal of cement smears and limescale



acid sensitive, scratch sensitive stone floors

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping	<input type="checkbox"/>			V <b>Masslinn 2000</b> Multi squeegee	<b>Balit with pad sole</b>	
1  dry vacuum cleaning	<input type="checkbox"/>			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Twinvac</b> Monovac Portovac	heavily soiled
<b>cleaning without maintenance</b>						
2  wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Polex</b> Rewit 2000	<b>0.5 - 1%</b> 0.5 - 1%	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush washbeton	<b>Monomatic I / LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	 
3  wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Calexan</b>	<b>100%</b>	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush washbeton	<b>Monomatic I / LS</b> <b>Twinvac / Duovac</b>	attention: modification of surface   
4  rinsing	<input type="checkbox"/>	<b>0</b>	<b>100%</b>	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush washbeton	<b>Monomatic I / LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	large areas: scrubber-dryer.  
4  rinsing	<input type="checkbox"/>	<b>0</b>	<b>100%</b>	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush washbeton	<b>Duo- / Discomatic</b> Sprinter / Drivematic	large areas  
5  wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Polex</b> Rewit 2000	<b>0.5 - 1%</b> 0.5 - 1%	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush soft	<b>Monomatic I / LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	
6  rinsing	<input type="checkbox"/>	<b>0</b>	<b>100%</b>	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush washbeton	<b>Monomatic I / LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	large areas: scrubber-dryer.  
6  rinsing	<input type="checkbox"/>	<b>0</b>	<b>100%</b>	 <b>Microsol fibre pad</b>  Pad red S  Scrubbing brush soft	<b>Duo- / Discomatic</b> Sprinter / Drivematic	large areas  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

**important:** Wet scrubbing 1 minute at most with sanitary basic cleaner, wet vacuuming instantly and rinse well. Repeat several times if needed.

# General instructions for cleaning and care

## no.42 Removal of cement smears and limescale



acid resistant and scratch sensitive stone floors

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning	<input type="checkbox"/>			V S V Dust roller nozzle Combi-nozzle	Twinvac Monovac Portovac	heavily soiled
1  dusting damp mopping	<input type="checkbox"/>			Masslinn 2000	Balit with pad sole	
<b>cleaning without maintenance</b>						
2  wet mopping single step	<input type="checkbox"/>	0	100%	Kentucky-mop		watering gouging. 
3  wet scrubbing and wet vacuuming	<input type="checkbox"/>	Calexan	100%	 Microsol fibre pad  Pad red S  Scrubbing brush washbeton	Monomatic I / LS Twinvac / Duovac	  
4  rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush washbeton	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer.  
4  rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush soft	Duo- / Discomatic Sprinter / Drivematic	large areas  
5  wet scrubbing and wet vacuuming	<input type="checkbox"/>	Polex	0.5 - 1%	 Microsol fibre pad  Pad red S  Scrubbing brush washbeton	Monomatic I / LS Watertank Twinvac / Duovac	
6 rinsing   	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad red S  Scrubbing brush washbeton	Monomatic I / LS Twinvac / Duovac Duo- / Discomatic	large areas: scrubber-dryer.  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

**important:** Wet scrubbing 1 minute at most with sanitary basic cleaner, wet vacuuming instantly and rinse well. Repeat several times if needed.  
 Sensitive or resistant against acid means against amidosulphuric acid.

# General instructions for cleaning and care

## no.42 Removal of cement smears and limescale



acid and scratch resistant stone floors

object \_\_\_\_\_  
 address \_\_\_\_\_  
 room classification \_\_\_\_\_

date \_\_\_\_\_  
 customer \_\_\_\_\_  
 representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	heavily soiled
1  dusting damp mopping	<input type="checkbox"/>			Masslinn 2000	Balit with pad sole	
<b>cleaning without maintenance</b>						
2  wet mopping single step	<input type="checkbox"/>	0	100%	Kentucky-mop		watering gouging. 
3  wet scrubbing and wet vacuuming	<input type="checkbox"/>	Calexan	100%	V  Microsol fibre pad S  Pad green S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac	  
4  rinsing	<input type="checkbox"/>	0	100%	V  Microsol fibre pad S  Pad green S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	large areas: scrubber-dryer.  
4  rinsing	<input type="checkbox"/>	0	100%	V  Microsol fibre pad S  Pad green S  Scrubbing brush Filament	Duo- / Discomatic Sprinter / Drivematic	large areas  
5  wet scrubbing and wet vacuuming	<input type="checkbox"/>	Polex	0.5 - 1%	V  Microsol fibre pad S  Pad green S  Scrubbing brush Filament	Monomatic I / LS Watertank Twinvac / Duovac	
6 rinsing   	<input type="checkbox"/>	0	100%	V  Microsol fibre pad S  Pad green S  Scrubbing brush Filament	Monomatic I / LS Twinvac / Duovac Duo- / Discomatic	large areas: scrubber-dryer.  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

**important:** Wet scrub for max 5 minutes with a sanitary basic cleaner then immediately wet vacuum and rinse well. Repeat several times if required. Sensitive or resistant against acid means against amidosulphuric acid.

## General instructions for cleaning and care



### no.42 Removal of cement smears and limescale

#### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrok.com](http://www.wetrok.com).  
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrok.com](http://www.wetrok.com).  
The recommended colours of pad and brushes consist to the actual wWetrok product range.  
Follow the special cleaning and care instructions of the floor manufacturer.  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



**Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.**  
**Strong acids can destroy limestone, slate and cement-bonded artificial stone.**  
**Strong alkalines can attack polished stone coverings and destroy the shine.**  
**Abrasive pads and brushes can destroy polishes, limestone, slate and cement-bonded artificial stone.**  
**Plastic-bonded synthetic stone is sensitive to solvents.**

Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.



Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

Hard types of stone, e.g. granite, gneiss, quartzite and porphyry, are largely acid resistant.

Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofer stone, travertine, slate or sandstone is sensitive to acid.

Sensitive or resistant against acid means against amidosulphuric acid.

The colour and the appearance of the stone varies depending on its origin.

Cast stone is laid as finished slabs and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or [academy@wetrok.ch](mailto:academy@wetrok.ch).