

General instructions for cleaning and care

no.31 Natural stone, acid-resistant (structured profile)
















cleaning system without treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓		cleaning method		recommendations * chemical products dosage		recommendations pad / brush / mop / cloth		recommendations machine / tool	comments
1		dry vacuum cleaning	<input type="checkbox"/>			V S	Dust roller nozzle	Twinvac Monovac Portavac	if needed
1		vacuum sweeping	<input type="checkbox"/>					Speedmatic Twister Master Sweep Turbo Sweep	large areas
2		dusting damp mopping	<input type="checkbox"/>			S S S	Synthetic fur Microsol cloth Synthetic fur	Balit with velcro	
cleaning without maintenance care product (if coating follows)									
3		wet mopping single step	<input type="checkbox"/>	V V	Ecofloor Reshine Antiwx forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Socar / Drewell Wetcar / Drewell Wetbox system	
3		scrubber drying single step	<input type="checkbox"/>	V V	Ecofloor Reshine Antiwx forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	⊙ ⊙ ⊙ Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	
3		wet scrubbing and wet vacuuming	<input type="checkbox"/>	V	Reshine Antiwx forte classic	1 - 2% 0.5 - 1%	⊙ ⊙ ⊙ Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled  
4		stain removal	<input type="checkbox"/>	See cleaning instruction no 42					if needed
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)									
5		wet mopping single step	<input type="checkbox"/>		Redur Remop	3 - 4% 2 - 3%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Socar / Drewell Wetcar / Drewell Wetbox system	
5		scrubber drying single step	<input type="checkbox"/>		Redur Remop	3 - 4% 2 - 3%	⊙ ⊙ ⊙ Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care


























no.31 Natural stone, acid-resistant (structured profile)



maintenance cleaning

work process: select one work stage from each number

object _____ date _____
 address _____ customer _____
 room classification _____ representative _____

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping				B S S Synthetic fur Microsol cloth	Balit with velcro	
1	 dry vacuum cleaning				V Dust roller nozzle	Monovac Portavac Twinvac	if needed
1	 vacuum sweeping sweeping					Speedmatic Twister Master Sweep Turbo Sweep	large areas
cleaning without maintenance							
2	  wet mopping single step		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Variwet handle	
2	 scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V    Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	
cleaning with maintenance							
3	  wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Variwet handle	
3	 scrubber drying single step		Redur Remop	1 - 4% 1 - 2%	V    Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care


















no.31 Natural stone, acid-resistant (structured profile)



interim cleaning

work process: select one work stage from each number

object _____ date _____
 address _____ customer _____
 room classification _____ representative _____

↓	cleaning method		freq uenc	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping					B S Synthetic fur S Microsol cloth	Balit with velcro	
1	 dry vacuum cleaning					V S Dust roller nozzle	Monovac Portavac Twinvac	if needed
1	 vacuum sweeping sweeping						Speedmatic Twister Master Sweep Turbo Sweep	large areas
cleaning without maintenance								
2	 wet mopping two-step			Reshine G Antiwax forte classic	2 - 5% 2 - 5%	V Microsmooth-mop Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	 
2	 scrubber drying two-step			Reshine G Antiwax forte classic	2 - 5% 2 - 5%	V  Microsol fibre pad  Scrubbing brush Filament  Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.
 For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no.31 Natural stone, acid-resistant (structured profile)



basic cleaning

object _____

date _____













































address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

	cleaning method		freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1		dry vacuum cleaning				V S Dust roller nozzle	Twinvac Monovac Portavac	if needed	
2		dusting damp mopping				B S Synthetic fur S Microsol cloth	Balit with velcro		
3		chewing gum removal		Karpfrost Karpotek	100% 100%			if needed	
cleaning without maintenance									
4		wet scrubbing and wet vacuuming		Antiwax forte classic 30 - 50% G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	V   	Monomatic I / LS Watertank Twinvac / Duovac	  	
4		scrubber drying two-step		Antiwax forte classic 30 - 50% G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	V   	Duo- / Discomatic Sprinter / Drivematic	large areas   	
5		rinsing		0	100%	V   	Monomatic I / LS Watertank Twinvac / Duovac	 	
5		rinsing		0	100%	V   	Duo- / Discomatic Sprinter / Drivematic	large areas  	
6		stain removal		See cleaning instruction no 42				if needed	
7		wet mopping single step		Biosan	3%	Silkysmooth-mop Microbrush-mop	Wetbox system Socar / Drewell	if needed, bad smell could be removed with  	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: Sensitive or resistant against acid means against amidosulphuric acid.

General instructions for cleaning and care

no.31 Natural stone, acid-resistant (structured profile)



protective treatment

object _____

date _____









address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method		recommendations * chemical products dosage		recommendations * pad / brush / mop / cloth		recommendations machine / tool	comments
1		dry vacuum cleaning <input type="checkbox"/>			V S	Dust roller nozzle	Twinvac Monovac Portavac	if needed
2		dusting damp mopping <input type="checkbox"/>			S S	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
coating								
3		impregnation <input type="checkbox"/>	F	Imprasol 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.  
coating								
3		coating <input type="checkbox"/>		Stoner 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	If necessary, one layer on porous surface.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: if needed

Sensitive or resistant against acid means against amidosulphuric acid.

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use.

do not coat impregnated floors.

Process treatment of protection: see description of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care

no.31 Natural stone, acid-resistant (structured profile)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.




Hard types of stone, e.g. granite, gneiss, quartzite and porphyry, are largely acid resistant.
Sensitive or resistant against acid means against amidosulphuric acid.
Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!

Fats and oils can penetrate into the stone covering. Stain formation!

Soak the joints well or saturate them with an alkali cleaning solution before removing cement residue or limescale.



Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.
The colour and the appearance of the stone varies depending on its origin.

Distinguishing feature: natural stone acid-proof acid assay: apply a little basic sanitary cleaner to the stone covering, does not foam up.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.