



no 39 Cement surface layer (smooth and coated)



	cleaning system without tend of construction	treatn			object ddress	8	date customer representative			
work	process: select one work stage from	m each		Toom oldoon	iou.ioi	·	_			
	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac			
1	brush vacuum cleaning	[S		Monovac / Picojet	for durable flooring only		
1	vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas		
2	chewing gum removal		Karpfrost Karpotek	100% 100%			Monovac Twinvac	if needed		
(cleaning without maintenance	care p			ī					
3	wet mopping single step		Ecofloor V Reshine V Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%		Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell		4	A S
3	scrubber drying single step		Ecofloor Reshine Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	> 000		Duo- / Discomatic Drivematic / Robomatic			
3	wet scrubbing and wet vacuuming		Reshine Antiwax forte classic	1 - 2% 0.5 - 1%	V 	Microsol fibre pad Scrubbing brush Filament Scrubbing brush washbeton	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled		<u>*</u>
4	stain removal		See cleaning instruction				<u> </u>	if needed		
	cleaning with maintenance car	e (first			duct		In / Discounti	ı		
5	scrubber drying single step		Redur Remop	3 - 4% 2 - 3%	v (0)		Duo- / Discomatic Drivematic / Robomatic	 		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled





no 39 Cement surface layer (smooth and coated)



maintenance cleaning				objectaddressroom classification			date customer representative	
work pr	ocess: select one work stage fro	m each	number	TOOTT Classii	ication		- representative	
C	leaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	
1	brush vacuum cleaning				V S		Monovac / Picojet	for durable flooring only
1	vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
cle	aning without maintenance							
2	wet mopping single step		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V	Micro nonwoven-1 Micro woven-1 Silkysmooth-1	Variwet Plus Socar / Drewell Variwet Plus	
2	scrubber drying single step		Ecofloor Libero Reshine	0.5 - 1% 0.5 - 3% 1 - 2%	\sim	Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Drivematic / Robomatic	
cle	aning with maintenance							
2	wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	spray mopping (wet mopping)		Redur Remop	1 - 4% 1 - 2%	V	Micro nonwoven-1 Micro woven-1 Silkysmooth-1	Variwet Plus Socar / Drewell Variwet Plus	
2	scrubber drying single step	[Redur Remop	1 - 4% 1 - 2%		Microsol fibre pad Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled





no 39 Cement surface layer (smooth and coated)



interim cleaning					object		_ date		
				ac	ddress		customer		
				room classif	ication		representative		
work	process: select one work stage fro	m each	number				_		
$\frac{1}{\sqrt{1}}$	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac		
1	brush vacuum cleaning				S		Monovac / Picojet	for durable flooring only	
1	vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas	
(cleaning without maintenance								
2	wet mopping two-step		Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	v s	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell		
2	scrubber drying two-step		Reshine Polex G Antiwax forte classic	2 - 5% 2 - 4% 2 - 5%	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		Duo- / Discomatic Sprinter / Drivematic		
2	wet mopping single step		Biosan	3%		Microsmooth-mop Silkysmooth-mop Micro woven-1	Wetbox system Wetcar / Drewell Variwet Plus	if needed, bad smell could be removed with	

important: For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled





no 39 Cement surface layer (smooth and coated)



basic cleaning				object 				
				dress		customer		
			oom classifi		representative			
work process: select one work stage from	each nun	nber			-			
cleaning method	*	recommendations chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
brush vacuum : cleaning				S		Monovac / Picojet	for durable floorir only	ng
dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac		
vacuum sweeping sweeping				V	Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas	
chewing gum removal		Karpotek Karpfrost	100% 100%			Monovac Twinvac	if needed	\boxtimes
cleaning without maintenance						I		
wet scrubbing and wet vacuuming	G	Antiwax forte classic Rewit 2000 Remat forte	10 - 20% 10 - 20%	v (()	Microsol fibre pad Scrubbing brush Filament Scrubbing brush washbeton	Monomatic I / LS Watertank Twinvac / Duovac		
scrubber drying two-step	. !!	Antiwax forte classic Rewit 2000 Remat forte	30 - 50% 10 - 20% 10 - 20%	v @	Microsol fibre pad Scrubbing brush Filament Scrubbing brush Supernylon	Duo- / Discomatic Drivematic / Robomatic	large areas	
4 rinsing	;	pure water	100%	v	Microsol fibre pad Scrubbing brush Filament Scrubbing brush washbeton	Monomatic I / LS Twinvac / Duovac Duo- / Discomatic		pH 7
5 stain removal		See cleaning instruction				 	if needed	
wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro nonwoven-1	Wetbox system Wetcar / Drewell Variwet Plus	if needed, bad smell could be removed with	

important: Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled



no 39 Cement surface layer (smooth and coated)



	protective treatment				object		date		_
				ac	ddress		customer		
				room classifi	cation		representative		
wo	rk process: select one work stage fro	m each	number			-	_		
$\hat{\mathbb{I}}$	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				S	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac		
	pore filling (only if necessary)								
2	pore filling		F Porosol	100%		Florfix Florfix-mop	Florfix Balit with velcro	If necessary, one layer on porous surface.	
	coating								
3	coating		Stoner Mepol HM	100% 100%		Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers	

important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled





no 39 Cement surface layer (smooth and coated)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.

Do not coat structured floor coverings.

Soft stone, e.g. marble, limestone (Jura-limestone, concha-limestone), Solnhofer stone, travertine, slate or sandstone is sensitive to acid.

Soft stone is sensitive to scratches, only use suitable pads and brushes.

Plastic-bonded synthetic stone is sensitive to solvents.

Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!

Cement consists of limestone, clay, sand and aggregates.

Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.

Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Cast stone is laid as plates and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.