no. 23 Hard xylolite surfacing



alaaning avatam with treatment

cleaning system with treatment	object		te
end of construction	address	custom	er
	room classification	representativ	/e
k process: select one work stage from each number			

work	work process: select one work stage from each number								
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac		
1	vacuum sweeping sweeping	[V		Speedmatic Twister Master Sweep Turbo Sweep	large areas	
1	dusting damp mopping	[B S	Masslinn 2000 Masslinn Microsol cloth	Balit with pad sole	if needed	
	cleaning without maintenance	e care	product (if coating follo						
2	wet mopping single step		Ecofloor V Reshine V Antiwax forte	0.5 - 1% 1 - 2% 0.5 - 1%		Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell		
2	scrubber drying single step		EcofloorV ReshineV Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	V	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic		
2	wet scrubbing and wet vacuuming	<u> </u>	Reshine V Antiwax forte classic	1 - 2% 0.5 - 1%	V	Microsol fibre pad Pad red Pad blue	Monomatic LS Watertank Twinvac / Duovac	heavily soiled	
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)									
3	wet mopping single step		Redur Remop F Brill	3 - 4% 2 - 3% 3 - 5%		Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop only.	
3	scrubber drying single step		Redur F Brill 2care	3 - 4% 3 - 5% 3 - 5%		Microsol fibre pad Pad red	Duo- / Discomatic Sprinter / Drivematic		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no. 23 Hard xylolite surfacing



maintenance cleaning

	maintenance cleaning			a	object ddress		_ date customer		
vork	process: select one work stage from	m each	number	room classif	ication		_ representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac		
1	vacuum sweeping sweeping						Speedmatic Twister Master Sweep Turbo Sweep	large areas	
1	dusting damp mopping				S B	Masslinn 2000 Synthetic fur Masslinn	Balit with pad sole Balit with velcro	if needed	
	cleaning without maintenanc	e							
2	wet mopping single step		Ecofloor V Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	v s	Microbrush-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell		*
2	spray mopping (wet mopping)		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V	Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole		
2	scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	В V	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic		
cleaning with maintenance									
2	wet mopping single step		Redur Remop F Brill	1 - 4% 1 - 2% 1 - 2%	V S	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	Brill should be used with Silkysmooth mop only.	
2	scrubber drying single step		Redur F Brill 2care	1 - 4% 1 - 2% 1 - 2%	B O	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled




no. 23 Hard xylolite surfacing



	interim cleaning				object ddress		_ date customer		_
wo	rk process: select one work stage fror	n each	number	room classif	ication		representative		
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac		
1	vacuum sweeping sweeping						Speedmatic Twister Master Sweep Turbo Sweep	large areas	
1	dusting damp mopping				S B	Masslinn 2000 Synthetic fur Masslinn	Balit with pad sole Balit with velcro	if needed	
	cleaning without maintenance	Э							
2	wet mopping two-step		Reshine G Antiwax forte classic	2 - 5% 2 - 5%		Microsmooth-mop Silkysmooth-mop	Wetcar / Drewell Socar / Drewell		
2	scrubber drying two-step		Reshine G Antiwax forte classic	2 - 5% 2 - 5%	B V	Microsol fibre pad Pad red Pad blue	Duo- / Discomatic Sprinter / Drivematic		
3	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro woven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with	

important: For initial cleaning after interim cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





	basic cleaning			a	object ddress		date customer		-
work	process: select one work stage from	each	number	room classif	ication		representative		
	•	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	if needed	
1	dusting damp mopping				B S	Masslinn 2000 Masslinn Synthetic fur	Balit with pad sole Balit with velcro		
2	chewing gum removal		Karpfrost Karpotek	100% 100%				if needed	\blacksquare
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming		B Relino G Rewit 2000 Antiwax forte classic	20 - 50% 10 - 20% 30 - 50%	B O	Pad blue	Monomatic I / LS Watertank Twinvac / Duovac	\boxtimes	
3	scrubber drying two-step		B Relino G Rewit 2000 Antiwax forte classic	20 - 50% 10 - 20% 30 - 50%	B V	Microsol fibre pad Pad blue Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas	
4	rinsing		0	100%		Microsol fibre pad Pad blue	Monomatic I / LS Watertank Twinvac / Duovac		pH 7
4	rinsing		0			•	Duo- / Discomatic Sprinter / Drivematic	large areas	pH 7
5	wet mopping single step		Biosan	3%		Silkysmooth-mop Microbrush-mop Micro woven 1	Wetbox system Wetcar / Drewell	if needed, bad smell could be	

important: For initial cleaning after basic cleaning, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





	protective treatment			а	object ddress		date customer	
work process: select one work stage from each number			room classification			representative		
7	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Twinvac Portavac	if needed
2	dusting damp mopping				S	Masslinn 2000 Synthetic fur	Balit with pad sole Balit with velcro	
	pore filling (only if necessar	y)						
2	pore filling	[]	F Porosol	100%		Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.
	coating							
3	coating	; 	Stoner Mepol HM Mepol H	100% 100% 100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
	coating							
2	impregnation		F Imprasol	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry! do not coat impregnated floors.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no. 23 Hard xylolite surfacing



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Magnesite is sensitive to acids and Iyes. Use a special basic linoleum cleaner!

Magnesite is sensitive to permanent exposure to moisture and must not be wet mopped for the first two weeks after installation. Magnesite is resistant to fats and oils.



Magnesite (stone wood, wood cement) is manufactured from magnesia, quartz powder, wood flour, fillers and oxides.

Magnesite is an industrial flooring for medium to heavy loads: resistant to wear and highly resistant to pressure.

Magnesite coverings are cast without joints or with expansion joints, or hand finished, or laid in slabs.

Distinguishing feature: acid assay: apply a little sanitary cleaner to the magnesite covering. Immediately foams up: material damage!



Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.