

# General instructions for cleaning and care

## no.24 Ceramic tiles, glazed



















cleaning system without treatment  
end of construction

object \_\_\_\_\_  
address \_\_\_\_\_  
room classification \_\_\_\_\_

date \_\_\_\_\_  
customer \_\_\_\_\_  
representative \_\_\_\_\_

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping <input type="checkbox"/>			S <b>Masslinn 2000</b> S Microsol cloth S Synthetic fur	<b>Balit with pad sole</b> Balit with velcro	
1  dry vacuum cleaning <input type="checkbox"/>			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Twinvac</b> Monovac Portovac	if needed
1  vacuum sweeping sweeping <input type="checkbox"/>			V	<b>Speedmatic Twister</b> Master Sweep Turbo Sweep	large areas
<b>cleaning without maintenance</b>					
2  wet mopping single step <input type="checkbox"/>	<b>Ecofloor</b> V Reshine V Antiwax forte classic	<b>0.5 - 1%</b> 1 - 2% 0.5 - 1%	V S <b>Silkysmooth-mop</b> Microsmooth-mop Microbrush-mop	<b>Wetbox system</b> Socar / Drewell Wetcar / Drewell	
2  scrubber drying single step <input type="checkbox"/>	<b>Ecofloor</b> V Reshine V Antiwax forte classic	<b>0.5 - 1%</b> 1 - 2% 0.5 - 1%	 <b>Microsol fibre pad</b> S  Scrubbing brush Filament S  Scrubbing brush Superylon	<b>Duo- / Discomatic</b> Sprinter / Drivematic	
2  wet scrubbing and wet vacuuming <input type="checkbox"/>	<b>Reshine</b> V Antiwax forte classic	<b>1 - 2%</b> 0.5 - 1%	 <b>Microsol fibre pad</b> S  Scrubbing brush washbeton S  Scrubbing brush Filament	<b>Monomatic LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	heavily soiled  
2  stain removal <input type="checkbox"/>	See cleaning instruction no 42				

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.24 Ceramic tiles, glazed



### maintenance cleaning

object \_\_\_\_\_

date \_\_\_\_\_













address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S <b>Masslinn 2000</b> S Microsol cloth S Synthetic fur	<b>Balit with pad sole</b> Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Monovac</b> Twinvac Portavac	if needed
1	 vacuum sweeping	<input type="checkbox"/>			V	<b>Speedmatic Twister</b> Master Sweep Turbo Sweep	large areas
<b>cleaning without maintenance</b>							
2	 wet mopping single step	<input type="checkbox"/>	<b>Ecofloor</b> Reshine Biosan	<b>0.5 - 1%</b> 1 - 2% 0.8 - 1.5%	V S <b>Microbrush-mop</b> Microsmooth-mop Silkysmooth-mop	<b>Wetbox system</b> Wetcar / Drewell Socar / Drewell	
2	 spray mopping (wet mopping)	<input type="checkbox"/>	<b>Ecofloor</b> Reshine Biosan	<b>0.5 - 1%</b> 1 - 2% 0.8 - 1.5%	V <b>Micro nonwoven-1-</b> Micro woven-1- Silkysmooth-1-	<b>Variwet handle</b> <b>Balit with velcro</b> <b>Micro velcro sole</b>	
2	 scrubber drying single step	<input type="checkbox"/>	<b>Ecofloor</b> Reshine Ceratop	<b>0.5 - 1%</b> 1 - 2% 0.5 - 1%	S  <b>Microsol fibre pad</b> S  Scrubbing brush Filament S  Scrubbing brush Supernylon	<b>Duo- / Discomatic</b> Sprinter / Drivematic	
2	 foam cleaning	<input type="checkbox"/>	See cleaning instruction no 43				

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.24 Ceramic tiles, glazed



### interim cleaning

object \_\_\_\_\_

date \_\_\_\_\_















address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S <b>Masslinn 2000</b> S Microsol cloth S Synthetic fur	<b>Balit mit Padsohle</b> Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Monovac</b> Twinvac Portavac	if needed
1	 vacuum sweeping sweeping	<input type="checkbox"/>			V	<b>Speedmatic Twister</b> Master Sweep Turbo Sweep	large areas
<b>cleaning without maintenance</b>							
2	 wet mopping two-step	<input type="checkbox"/>	<b>Reshine</b> Ceratop Polex	<b>2 - 5%</b> 2 - 5% 2 - 4%	V S <b>Microsmooth-mop</b> Silkysmooth-mop	<b>Socar / Drewell</b> Wetcar / Drewell	
2	 scrubber drying two-step	<input type="checkbox"/>	<b>Reshine</b> Ceratop Polex	<b>2 - 5%</b> 2 - 5% 2 - 4%	S  <b>Microsol fibre pad</b> S  Scrubbing brush Filament S  Scrubbing brush Supernylon	<b>Duo- / Discomatic</b> Sprinter / Drivematic	
2	 foam cleaning	<input type="checkbox"/>	See cleaning instruction no 43				
3	 wet mopping single step	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>	<b>Microsmooth-mop</b> Silkysmooth-mop Micro nonwoven-1-	<b>Wetbox system</b> Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

# General instructions for cleaning and care

## no.24 Ceramic tiles, glazed



### basic cleaning

object \_\_\_\_\_

date \_\_\_\_\_



























address \_\_\_\_\_

customer \_\_\_\_\_

work process: select one work stage from each number

room classification \_\_\_\_\_

representative \_\_\_\_\_

↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S <b>Masslinn 2000</b> S Microsol cloth S Synthetic fur	<b>Balit with pad sole</b> Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S <b>Dust roller nozzle</b> V Combi-nozzle	<b>Twinvac</b> Monovac Portavac	if needed
2	 chewing gum removal	<input type="checkbox"/>	<b>Karpfrost</b> Karpotek	<b>100%</b> 100%			if needed 
<b>cleaning without maintenance</b>							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	<b>Antiwax forte classic</b> 30 - 50% Remat	10 - 20%	S  <b>Microsol fibre pad</b> S  Scrubbing brush washbeton S  Scrubbing brush Filament	<b>Monomatic I / LS</b> <b>Watertank</b> <b>Twinvac / Duovac</b>	 
3	 scrubber drying two-step	<input type="checkbox"/>	<b>Antiwax forte classic</b> 30 - 50% Remat	10 - 20%	S  <b>Microsol fibre pad</b> S  Scrubbing brush Filament S  Scrubbing brush Supernylon	<b>Duo- / Discomatic</b> Sprinter / Drivematic	large areas  
3	 foam cleaning	<input type="checkbox"/>	See cleaning instruction no 43				
4	 rinsing	<input type="checkbox"/>		<b>0 100%</b>	S  <b>Microsol fibre pad</b> S  Scrubbing brush Filament S  Scrubbing brush Supernylon	<b>Monomatic I / LS</b> <b>Twinvac / Duovac</b> Duo- / Discomatic	pH 7 
5	 stain removal	<input type="checkbox"/>	See cleaning instruction no 42				if needed
6	 wet mopping single step	<input type="checkbox"/>	<b>Biosan</b>	<b>3%</b>	<b>Silkysmooth-mop</b> Microbrush-mop Micro nonwoven-1-	<b>Wetbox system</b> Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with  

\* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

## General instructions for cleaning and care


### no.24 Ceramic tiles, glazed



#### Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.  
For security information, see the safety data sheet at [www.wetrok.com](http://www.wetrok.com).  
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.  
Follow the information and remarks on the label, product data sheet and material safety data sheet.  
The product data sheet describes the product and gives information about its application, storage. See [www.wetrok.com](http://www.wetrok.com).  
The recommended colours of pad and brushes consist to the actual wWetrok product range.  
Follow the special cleaning and care instructions of the floor manufacturer.  
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



#### **Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.**

The glaze is sensitive to scratching. Do not use abrasive pads or brushes!  
Ceramic floor coverings are generally acid resistant.  
Souring can cause discolouration in the glaze. Check the glaze for acid resistance beforehand.  
Do not use wipe and care cleaners in wet rooms and hygiene rooms.  
Do not use maintenance products on glazed tiles.



Ceramic floor coverings are heterogeneous products made from clay and aggregates such as feldspar and fluorite.  
The higher the firing temperature and the longer the time spent in the oven, the denser and more strongly sintered the ceramic will be.  
Earthenware: high water absorption (approx. 1,000°C), glazed earthenware: low water absorption (1,300°C).  
The glaze is melted in a second firing.  
Slip resistance in commercial areas: classification R9 - R13 (low to very high) and V4 - V10, in bare foot areas A,B,C.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.  
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.  
Test on an inconspicuous spot to find which product is suitable for your requirements.  
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.  
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.  
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or [academy@wetrok.ch](mailto:academy@wetrok.ch).

**Wetrok AG** Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, [info@wetrok.ch](mailto:info@wetrok.ch), [www.wetrok.com](http://www.wetrok.com).