

no.51 Wood or cork parquet (sealed)



cleaning system with treatment end of construction

date	object
customer	address
representative	room classification

work	work process: select one work stage from each number								
			recommendations			recommendations	recommendations		
ζ,	cleaning method		* chemical products	dosage	*	pad / brush / mop / cloth	machine / tool	comments	
	dusting	:				Masslinn 2000	Balit with pad sole		
1	damp mopping	il.			S	Microsol cloth	Balit with velcro		
		<i>-</i> '			S	Synthetic fur			
_	dry vacuum	:			V S	Dust roller nozzle	Twinvac	L	
1	cleaning	ij			V	Combi-nozzle	Monovac	if needed	
							Portavac		
	cleaning without maintenance	_					Trace of		
•	wet mopping	:	Ecofloor	0.5 - 1%		Microbrush-mop	Wetbox system		
2	single step	i	Reshine	1 - 2%	., .	Microsmooth-mop	Socar / Drewell		
			V Antiwax forte classic	0.5 - 1%	V S	Silkysmooth-mop	Wetcar / Drewell		
•	scrubber drying !-	:	Ecofloor	0.5 - 1%	۱., 💆	Pad red	Duo- / Discomatic	<u></u>	
2	single step	į	Reshine	1 - 2%	V @	Microsol fibre pad	Sprinter / Drivematic	丁	
			V Antiwax forte classic	0.5 - 1% 1 - 2%		Pad red	Monomatic I / LS		
2	wet scrubbing and ¦	!	Reshine		l., 🔀			heavily soiled	
2	wet vacuuming	;	Polex V Antiwax forte classic	0.5 - 1% 0.5 - 1%	V (S	Microsol fibre pad	Watertank Twinvac / Duovac	rieavily solled	
	cleaning with maintenance care				roduc	t as in maintenance cleaning)			
		- (111 \$	Redur	3 - 4%	loudo	Microbrush-mop	Socar / Drewell		
3	wet mopping	!	Remop	2 - 3%		Microsmooth-mop	Wetcar / Drewell		
Ū	single step	i	F Brill	3 - 5%	v s	Silkysmooth-mop	Wetbox system		
		,	Redur	3 - 4%	T	Pad red	Duo- / Discomatic		
3	scrubber drying	ij	Remop	2 - 3%			Sprinter / Drivematic		
	single step	'	F Brill	3 - 5%		Wildredge Haro pad	opinitor / Brivomatio	J	
		,	Waxspray	100%		Pad red	Monomatic DS		
3	spray cleaning	į	Elfspray	100%	lp 🔾	HS-Polish pad beige	Spray unit	after polishing	
	full spray	'	Polish	30%	lp Č) HS-Polish pad white			
	first protective treatment (with t	he s	ame product as in main	tenance <u>cle</u>	aning				
	1-	,	Polish	100%		Cover for Florfix	Florfix	Jun 9	
3	waxing	!			P C	HS-Polish pad beige	Monomatic HS	if needed HS	
		'			PC	HS-Polish pad white			

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled



no.51 Wood or cork parquet (sealed)

wetrok

maintenance cleaning

 date	ject	object
customer	ess	address
representative	tion	room classification

work process: select one work stage from each number

work	work process: select one work stage from each number									
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping	 			S F S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	if needed		
	cleaning without maintenand	е								
2	wet mopping single step	 	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	v s	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	if needed		
2	spray mopping (wet mopping)	<u> </u>	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%		Microbrush-mop Micro woven-1- Micro nonwoven-1-	Wetbox system Socar / Drewell Variwet handle	→		
2	scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	v S	Pad red Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	if needed		
	cleaning with maintenance									
2	wet mopping single step		Redur Remop F Brill	1 - 4% 1 - 2% 1 - 2%	v s	Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	if needed		
2	scrubber drying single step	[]	Redur Remop F Brill	1 - 4% 1 - 2% 1 - 2%	v S	Pad red Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	if needed		
2	spray cleaning partial / full spray		Waxspray Elfspray C Polish	100% 100% 30%	P C	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: When spray cleaning, you should change your pad often.



no.51 Wood or cork parquet (sealed)



ID+0	rim	α	anina
11111		L.IE	aning
		0.0	a

interim cleaning	object	date	
	address	customer	
	room classification	representative	
ork process: select one work stage from each number			

work	work process: select one work stage from each number									
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping	,,			S F S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
1	dry vacuum cleaning	,,			V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed		
	cleaning without maintenand	е								
2	wet mopping two-step	,,	Reshine G Antiwax forte G Antiwax forte classic	2 - 5% 2 - 5% 2 - 5%		Microbrush-mop Silkysmooth-mop	Wetcar / Drewell Socar / Drewell	→		
2	scrubber drying two-step		Reshine G Antiwax forte G Antiwax forte classic	2 - 5% 2 - 5% 2 - 5%		Pad red Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	* • •		
	cleaning with maintenance									
2	spray cleaning full spray	,,	Waxspray Elfspray C Polish	100% 100% 30%	P C	Pad red HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing		

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after interim cleaning, see "initial cleaning".

When spray cleaning, you should change your pad often.

spray cleaning

full spray

rinsing

rinsing



3



basic cleaning

no.51 Wood or cork parquet (sealed)



date

Monomatic DS

Monomatic I / LS

Twinvac / Duovac

Duo- / Discomatic

Sprinter / Drivematic

after spray clea 🚅

not necessary.

large

areas

pH 7

Spray unit

Watertank

	address				3	customer				
				room classif	ication	1	representative	:		
work	process: select one work stage fro	m each	number				_			
	cleaning method	freq uenc	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments		
1	dusting damp mopping				S F S	Masslinn Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro			
1	dry vacuum cleaning				V S V S	Dust roller nozzle Combi-nozzle	Twinvac Monovac Portavac	if needed		
2	chewing gum removal		Karpotek Karpfrost	100% 100%				if needed		
	cleaning without maintenanc	е								
3	wet scrubbing and wet vacuuming		Antiwax forte Relino Antiwax forte classic	30 - 50% 20 - 50% 30 - 50%	В	Pad blue Microsol fibre pad	Monomatic I / LS Watertank Twinvac / Duovac	heavily soiled	*	<u>*</u>
3	scrubber drying two-step		Antiwax forte Relino Antiwax forte classic	30 - 50% 20 - 50% 30 - 50%	В	Pad blue Microsol fibre pad	Duo- / Discomatic Sprinter / Drivematic	large areas	*	<u>*</u>

C Pad red

B Pad blue

Pad red

Pad red

Microsol fibre pad

Microsol fibre pad

object

100%

100%

important: Use a coin or a key to do a scratch test, to check if all the protective coating has been removed.

When white abrasion occurs, carry out a full clean to remove all the protective coating.

Antiwax forte classic 30 - 50%

For initial cleaning after basic cleaning, see "initial cleaning".

pure water

pure water

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





no.51 Wood or cork parquet (sealed)



date

protective treatment

	•			ad	dress	3	customer	
				room classific	cation	1	representative	
ork	c process: select one work stage fro	m each	number				_	
	cleaning method		recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping	<u></u> ;			S F C	Masslinn 2000 Microsol cloth Synthetic fur	Balit with pad sole Balit with velcro	
1	dry vacuum cleaning				V S V	Dust roller nozzle Combi-nozzle	Monovac Portavac Twinvac	if needed
	first protective treatment (wit	h the s			ning			
2	spray cleaning full spray		Waxspray Elfspray Polish	100% 100% 30%	C	HS-Polish pad beige HS-Polish pad white	Monomatic DS Spray unit	after polishing
	coating							
2	waxing		Polish	100%		Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers
	buffing wax treatment (only it	f neces	sary)					
3	dusting damp mopping					Masslinn 2000	Balit with pad sole	if needed
4	нs рolishing, vacuum polishing	[]			c c	HS-Polish pad beige HS-Polish pad white	Monomatic HS Suction ring	after polishing

obiect

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

When spray cleaning, you should change your pad often.

Let dry protection treatment completely between the layers and before use.

Process treatement of protection: see descriptione of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled





no.51 Wood or cork parquet (sealed)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong alkalines can destroy or discolour wood coverings. Use a special basic linoleum cleaner!

Wood coverings are sensitive to abrasive pads and brushes.

Factory sealed parquet is water sensitive. Water can penetrate into the wood covering through the joints.

Permanent exposure to moisture should be avoided with wood coverings. Mop as little as possible and wring out the mop thoroughly.

Allow it to dry completely before applying a protective treatment! Allow longer drying times than for non-porous coverings such as PVC.



Hardwoods (deciduous wood) such as oak, beech, ash, maple, walnut and acacia, or exotic woods, are processed into parquet.

Softwoods (coniferous wood) such as spruce, fir and pine are mostly used in the manufacturing of floor boards (long tongue-and-groove boards).

Certain manufacturers seal the wood coverings at the factory.

Humidity variations cause wood to shrink (dry out) or swell (exposure to moisture) and, possibly, warp (moisture).

Distinguishing feature: appearance of wood, dull sound when tapped.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.