

General instructions for cleaning and care

no.27 Synthetic stone, polished, paving stones and Terrazzo




























cleaning system with treatment
end of construction

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method	recommendations * chemical products	dosage	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting damp mopping <input type="checkbox"/>			S Masslinn 2000 Microsol cloth Multi squeegee	Balit with pad sole	
1  dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	if needed
cleaning without maintenance care product (if coating follows)					
2  wet mopping single step <input type="checkbox"/>	V Ecofloor V Reshine V Antiwax forte	0.5 - 1% 1 - 2% 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2  scrubber drying single step <input type="checkbox"/>	V Ecofloor V Reshine V Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	V  Microsol fibre pad V  Pad blue V  Pad green	Duo- / Discomatic Sprinter / Drivematic	green and black pad on hard stone only !
2  wet scrubbing and wet vacuuming <input type="checkbox"/>	V Reshine V Antiwax forte classic	1 - 2% 0.5 - 1%	V  Microsol fibre pad V  Pad blue V  Pad green	Monomatic LS Watertank Twinvac / Duovac	heavily soiled  
3  stain removal <input type="checkbox"/>	See cleaning instruction no 42				if needed
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)					
4  wet mopping single step <input type="checkbox"/>	F Redur Remop Brill	3 - 4% 2 - 3% 3 - 5%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	Brill should be used with Silkysmooth mop only. 
4  scrubber drying single step <input type="checkbox"/>	F Redur Remop Brill	3 - 4% 2 - 3% 3 - 5%	V  Microsol fibre pad V  Pad red	Duo- / Discomatic Sprinter / Drivematic	
4  spray cleaning full spray <input type="checkbox"/>	Polyspray Elspray	100% 100%	V  Pad red P  HS-Polish pad beige P  HS-Polish pad white	Monomatic DS Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.27 Synthetic stone, polished, paving stones and Terrazzo



maintenance cleaning

object _____

date _____




























address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			Masslinn S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	
cleaning without maintenance							
2	 wet mopping single step	<input type="checkbox"/>	Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2	 spray mopping (wet mopping)	<input type="checkbox"/>	Ecofloor Reshine Biosan	0.5 - 1% 1 - 2% 0.8 - 1.5%	V Micro nonwoven-1- Micro woven-1- Silkysmooth-1-	Variwet handle Balit with velcro Micro velcro sole	
2	 scrubber drying single step	<input type="checkbox"/>	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V  Microsol fibre pad  Pad red  Pad blue	Duo- / Discomatic Sprinter / Drivematic	
2	 HS polishing, vacuum polishing	<input type="checkbox"/>			B  HS-Polish pad beige B  HS-Polish pad white	Monomatic HS Suction ring Monoma Monomatic US	after polishing 
cleaning with maintenance							
2	 wet mopping single step	<input type="checkbox"/>	Redur Remop Brill	1 - 4% 1 - 2% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	Brill should be used with Silkysmooth mop only.
2	 scrubber drying single step	<input type="checkbox"/>	Redur Remop Brill	1 - 4% 1 - 2% 1 - 2%	V  Microsol fibre pad  Pad red  Pad blue	Duo- / Discomatic Sprinter / Drivematic	
2	 spray cleaning partial / full spray	<input type="checkbox"/>	Polyspray Elfspray Polish	100% 100% 30%	P  Pad red P  HS-Polish pad beige P  HS-Polish pad white	Monomatic DS Spray unit	after polishing 
2	 US spray cleaning full spray	<input type="checkbox"/>	B US Restorer	100%	B  US-Polish pad beige	Monomatic US Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.27 Synthetic stone, polished, paving stones and Terrazzo



interim cleaning

object _____

date _____























address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			F Masslinn 2000 B Masslinn B S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac Portavac	if needed
cleaning without maintenance							
2	 wet mopping two-step	<input type="checkbox"/>	Reshine G Antiwax forte classic	2 - 5% 2 - 5%	Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	 
2	 scrubber drying two-step	<input type="checkbox"/>	Reshine G Antiwax forte classic	2 - 5% 2 - 5%	 Microsol fibre pad  Pad red  Pad blue	Duo- / Discomatic Sprinter / Drivematic	 
2	 wet mopping single step	<input type="checkbox"/>	Biosan	3%	V S Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetbox system	if needed, bad smell could be removed with  
cleaning with maintenance							
3	 spray cleaning full spray	<input type="checkbox"/>	Polyspray Elfspray Polish	100% 100% 30%	 Pad red P  HS-Polish pad beige P  HS-Polish pad white	Monomatic DS Spray unit	after polishing 
3	 US spray cleaning full spray	<input type="checkbox"/>	B US Restorer	100%	B  US-Polish pad beige	Monomatic US Spray unit	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no.27 Synthetic stone, polished, paving stones and Terrazzo



basic cleaning

object _____

date _____






























address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			B Masslinn F Masslinn 2000 B S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portovac	if needed
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed 
cleaning without maintenance							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	B Remat forte B Relino Antiwax forte classic	10 - 20% 20 - 50% 30 - 50%	 Microsol fibre pad B  Pad green	Monomatic I / LS Watertank Twinvac / Duovac	  
3	 scrubber drying two-step	<input type="checkbox"/>	B Remat B Relino Antiwax forte classic	10 - 20% 20 - 50% 30 - 50%	 Microsol fibre pad B  Pad green	Duo- / Discomatic Sprinter / Drivematic	large areas   
3	 rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad blue	Monomatic I / LS Watertank Twinvac / Duovac	 
3	 rinsing	<input type="checkbox"/>	0	100%	 Microsol fibre pad  Pad blue	Duo- / Discomatic Sprinter / Drivematic	large areas  
4	 wet mopping single step	<input type="checkbox"/>	Biosan	3%	Silksmooth-mop Microsmooth-mop Micro nonwoven-1-	Wetbox system Wetcar / Drewell Variwet handle	if needed, bad smell could be removed with  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: green and black pad on hard stone only !
For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care

no.27 Synthetic stone, polished, paving stones and Terrazzo



protective treatment

object _____

date _____

















address _____

customer _____

work process: select one work stage from each number

room classification _____

representative _____

↓	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping <input type="checkbox"/>			Masslinn 2000 S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
pore filling (only if necessary)						
2	 pore filling <input type="checkbox"/>	Porosol	100%	Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.  
coating						
3	 coating <input type="checkbox"/>	Stoner Mepol HM	100% 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
3	 waxing <input type="checkbox"/>	Polish	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
buffing wax treatment (only if necessary)						
4	 dusting damp mopping <input type="checkbox"/>			Masslinn 2000	Balit with pad sole	if needed
4	 HS polishing, vacuum polishing <input type="checkbox"/>			C ○ HS-Polish pad white	Monomatic HS 0 Suction ring	after polishing 
coating						
2	 impregnation <input type="checkbox"/>	Imprasol	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	If necessary, one layer on porous surface.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!
do not coat impregnated floors.
Process treatment of protection: see description of method.
For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care


no.27 Synthetic stone, polished, paving stones and Terrazzo



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Strong acids can destroy cement-bound synthetic stone.
Cement-bound synthetic stone is sensitive to solvents.
Most grouts are acid sensitive. Soak the joints well before using acidic cleaners.

There must be no coating in the open air and in wet rooms. Danger of slipping!
There must be no coating in the open air and in wet rooms. Danger of slipping!



Synthetic stone is a blend of coloured stone chippings in cement or bound with a resin.
Cast stone is laid as finished slabs and terrazzo is poured and ground across the entire surface.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, telephone +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.com.