

General instructions for cleaning and care




















no.4 Rubber studs

**cleaning system without treatment
end of construction**

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

↓	cleaning method	recommendations * chemical products	dosage	* pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting  damp mopping			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	if needed
1	 vacuum sweeping sweeping				Speedmatic Twister Turbo Sweep	large areas
cleaning without maintenance care product (if coating follows)						
2	  wet mopping single step	V Ecofloor V Reshine V Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	V S Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2	  wet scrubbing and wet vacuuming	Antiwax forte classic Antiwax	30 - 50% 10 - 30%	⊙ Scrubbing brush washbeton ⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon	Monomatic LS Watertank Twinvac / Duovac	  
2	 scrubber drying two-step	Antiwax forte classic Antiwax	30 - 50% 10 - 30%	⊙ Scrubbing brush washbeton ⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	  
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)						
2	 scrubber drying single step	Redur Remop	3 - 4% 2 - 3%	⊙ Scrubbing brush washbeton ⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	without protective treatment.

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: repeat until separating agent is completely removed.

General instructions for cleaning and care
















no.4 Rubber studs

maintenance cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting damp mopping	<input type="checkbox"/>			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac Portavac	if needed
1	 vacuum sweeping sweeping	<input type="checkbox"/>			V	Speedmatic Twister Turbo Sweep	large areas
cleaning without maintenance							
3	 wet mopping single step	<input type="checkbox"/>	Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S Silkysmooth-mop Microsmooth-mop Microbrush-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
3	 scrubber drying single step	<input type="checkbox"/>	Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush soft ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	
3	 HS polishing, vacuum polishing	<input type="checkbox"/>			B  Polishing brush Union  Microsol fibre pad	Monomatic HS Suction unit Suction ring	after polishing 
cleaning with maintenance							
3	 wet mopping single step	<input type="checkbox"/>	Redur Remop	1 - 4% 1 - 2%	V S Silkysmooth-mop Microsmooth-mop Microsmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
3	 scrubber drying single step	<input type="checkbox"/>	Redur Remop	1 - 4% 1 - 2%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush soft ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

















no.4 Rubber studs

interim cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting  damp mopping	<input type="checkbox"/>			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Monovac Twinvac Portavac	if needed
1	 vacuum sweeping	<input type="checkbox"/>			V	Speedmatic Twister Turbo Sweep	large areas
cleaning without maintenance							
2	 wet mopping two-step	<input type="checkbox"/>	Reshine G Rewit 2000 V Antiwax forte classic	2 - 5% 2 - 5% 2 - 5%	V S Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	 
2	 scrubber drying two-step	<input type="checkbox"/>	Reshine G Rewit 2000 V Indumat	2 - 5% 2 - 5% 2 - 5%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush soft ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Sprinter / Drivematic	 
2	 HS polishing, vacuum polishing	<input type="checkbox"/>			B  Polishing brush Union  Microsol fibre pad	Monomatic HS Suction unit Suction ring	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care






















no.4 Rubber studs

basic cleaning

object _____
 address _____
 room classification _____

date _____
 customer _____
 representative _____

work process: select one work stage from each number

↓	cleaning method	freq uenc	recommendations * chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dusting  damp mopping	<input type="checkbox"/>			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
1	 dry vacuum cleaning	<input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Monovac Portavac	if needed
2	 chewing gum removal	<input type="checkbox"/>	Karpfrost Karpotek	100% 100%			if needed 
cleaning without maintenance							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Relino Rewit 2000 Antiwax forte classic	20 - 50% 10 - 20% 30 - 50%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush washbeton	Monomatic LS Watertank Twinvac / Duovac	  
3	 scrubber drying two-step	<input type="checkbox"/>	Relino Rewit 2000 Antiwax forte classic	20 - 50% 10 - 20% 30 - 50%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon ⊙ Scrubbing brush soft	Duo- / Discomatic Sprinter / Drivematic	large areas   
4	 rinsing	<input type="checkbox"/>	pure water	100%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon ⊙ Scrubbing brush soft	Monomatic LS Watertank Twinvac / Duovac	 
4	 rinsing	<input type="checkbox"/>	pure water	100%	⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon ⊙ Scrubbing brush soft	Duo- / Discomatic Sprinter / Drivematic	large areas  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: repeat until separating agent is completely removed.
 For initial cleaning after basic cleaning, see "initial cleaning".

General instructions for cleaning and care
















no.4 Rubber studs

protective treatment

object _____ date _____
 address _____ customer _____
 room classification _____ representative _____

work process: select one work stage from each number

cleaning method	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1  dusting  damp mopping			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
1  dry vacuum cleaning			V S Dust roller nozzle V Combi-nozzle	Monovac Portavac Twinvac	
coating					
2  coating	Mepol HM Stoner	100% 100%	Cover for Florfix Balit with velcro ☉ Shampooing brush	Florfix Florfix-mop Monomatic LS	1 - 3 thin layers  
2  waxing	Polish	100%	Cover for Florfix Balit with velcro ☉ Shampooing brush	Florfix Florfix-mop Monomatic LS	1 - 3 thin layers  
buffing wax treatment (only if necessary)					
3  dusting  damp mopping			S Microsol cloth S Synthetic fur	Balit with pad sole Balit with velcro	
4  polishing, vacuum polishing			C ○ HS-Polish pad white C ○ Polishing brush Union	Monomatic HS Suction unit Suction ring	after polishing 

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: Disinfection / P: polishing / S: structured / V: heavily soiled

important: if needed

Do not coat floors with PUR coating provided in the factory !

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Process treatment of protection: see description of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care



no.4 Rubber studs

Information about the flooring




Wetrok AG cannot accept any liability for damages due to improper use.
For security information, see the safety data sheet at www.wetrok.com.
Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.
Follow the information and remarks on the label, product data sheet and material safety data sheet.
The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.
The recommended colours of pad and brushes consist to the actual wWetrok product range.
Follow the special cleaning and care instructions of the floor manufacturer.
The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Rubber-studded floor coverings are sensitive to strong alkalines such as soft soap and basic cleaners. Colour change: material damage!

Rubber-studded floor coverings are sensitive to certain solvents such as ketone and ester.

Fat-soluble colorants such as shoe polish or asphalt can penetrate into rubber-studded floor coverings: diffusion.
Mould-release agents from production (silicone or paraffin-based) must be completely removed before basic treatment.
Paraffin-like antioxidants can migrate to the surface over time and form white clouds. These can be polished out.
Rubber-studded floor coverings with low studs can be spray cleaned.



Rubber-studded floor coverings are a blend of synthetic and natural rubber, sulphur (vulcanising agent), fillers and colour pigments.

Distinguishing feature: fire assay with a glowing hot needle in an inconspicuous place: the needle penetrates only slightly, typical rubber smell, no crater formation.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.
Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.
Test on an inconspicuous spot to find which product is suitable for your requirements.
Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.
Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.
For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.