

General instructions for cleaning and care

no 40  **Cement surface layer (rough)**





















**cleaning system without treatment
end of construction**

object _____
address _____
room classification _____


date _____
customer _____
representative _____

work process: select one work stage from each number

cleaning method		* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning <input type="checkbox"/>			V S Dust roller nozzle V Combi-nozzle	Twinvac Duovac Portavac	
1	 vacuum sweeping <input type="checkbox"/>			V Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
1	 dusting damp mopping <input type="checkbox"/>			B Masslinn 2000 S Microsol cloth V B Multi squeegee	Balit with pad sole	if needed
cleaning without maintenance care product (if coating follows)						
2	 wet mopping single step <input type="checkbox"/>	Ecofloor V Indumat V Antiwax forte classic	0.5 - 1% 0.5 - 1% 0.5 - 1%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Socar / Drewell Wetcar / Drewell Wetbox system	
2	 scrubber drying single step <input type="checkbox"/>	Ecofloor V Reshine V Antiwax forte classic	0.5 - 1% 1 - 2% 0.5 - 1%	 Microsol fibre pad Pad blue S  Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	
2	 wet scrubbing and wet vacuuming <input type="checkbox"/>	Ecofloor Antiwax forte classic Reshine	0.5 - 1% 0.5 - 1% 1 - 2%	 Microsol fibre pad Pad blue S  Scrubbing brush Filament	Monomatic LS Watertank Twinvac / Duovac	heavily soiled  
cleaning with maintenance care (first protective treatment with same product as in maintenance cleaning)						
3	 wet mopping single step <input type="checkbox"/>	Redur Remop	3 - 4% 2 - 3%	Silkysmooth-mop Microsmooth-mop Microbrush-mop	Socar / Drewell Wetcar / Drewell Wetbox system	
3	 scrubber drying single step <input type="checkbox"/>	Redur Remop	3 - 4% 2 - 3%	 Microsol fibre pad Pad blue S  Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care




























no 40  **Cement surface layer (rough)**



maintenance cleaning

object _____ date _____
address _____ customer _____
room classification _____ representative _____

work process: select one work stage from each number

	↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1		dry vacuum cleaning				V S Dust roller nozzle V Combi-nozzle	Monovac Portavac Twinvac	
1		vacuum sweeping sweeping				V Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
1		dusting damp mopping				B Masslinn B S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	if needed
cleaning without maintenance								
2		wet mopping single step		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Wetcar / Drewell Socar / Drewell	
2		spray mopping (wet mopping)		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%	Microbrush-mop Micro woven-1 Micro nonwoven-1	Variwet Plus Balit with velcro Micro velcro sole	
2		scrubber drying single step		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	
cleaning with maintenance								
2		wet mopping single step		Redur Remop	1 - 4% 1 - 2%	V S Microbrush-mop Microsmooth-mop Silkysmooth-mop	Wetbox system Socar / Drewell Wetcar / Drewell	
2		spray mopping (wet mopping)		Redur Remop	1 - 4% 1 - 2%	V Micro nonwoven-1 Micro woven-1 Silkysmooth-1	Variwet Plus Balit with velcro Micro velcro sole	
2		scrubber drying single step		Redur Remop	1 - 4% 1 - 2%	 Microsol fibre pad  Pad red S  Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

General instructions for cleaning and care

no 40  **Cement surface layer (rough)**


















interim cleaning

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

	↓	cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1		dry vacuum cleaning	<input type="checkbox"/>			F S Dust roller nozzle F Combi-nozzle	Monovac Portavac Twinvac	
1		vacuum sweeping sweeping	<input type="checkbox"/>			V Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
1		dusting damp mopping	<input type="checkbox"/>			B Masslinn B S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	if needed
cleaning without maintenance								
2		wet mopping two-step	<input type="checkbox"/>	Reshine G Rewit 2000	2 - 5% 2 - 5%	V S Microsmooth-mop Silkysmooth-mop	Socar / Drewell Wetcar / Drewell	 
2		scrubber drying two-step	<input type="checkbox"/>	Reshine G Rewit 2000	2 - 5% 2 - 5%	 Microsol fibre pad  Pad blue S  Scrubbing brush Filament	Duo- / Discomatic Drivematic / Robomatic	 
3		wet mopping single step	<input type="checkbox"/>	Biosan	3%	Silkysmooth-mop Microbrush-mop Micro woven-1	Wetbox system Wetcar / Drewell Variwet Plus	if needed, bad smell could be removed with  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

important: For initial cleaning after interim cleaning, see "initial cleaning".

General instructions for cleaning and care

no 40 Cement surface layer (rough)























basic cleaning

object _____
address _____
room classification _____

date _____
customer _____
representative _____

work process: select one work stage from each number

	↓ cleaning method	freq uenc	* recommendations chemical products	dosage	* recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning	<input type="checkbox"/>			F S Dust roller nozzle F Combi-nozzle	Monovac Portavac Twinvac	
1	 vacuum sweeping sweeping	<input type="checkbox"/>			V Carpet set - Twister	Speedmatic Twister Master Sweep Turbo Sweep	large areas
1	 dusting damp mopping	<input type="checkbox"/>			B Masslinn 2000 B S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	if needed
2	 chewing gum removal	<input type="checkbox"/>	Karpotek Karpfrost	100% 100%		Monovac Portavac Twinvac	if needed 
cleaning without maintenance							
3	 wet scrubbing and wet vacuuming	<input type="checkbox"/>	Antiwax forte classic 30 - 50% G Rewit 2000 10 - 20% B Relino 20 - 50%		⊙ Scrubbing brush Filament ⊙ Scrubbing brush washbeton B ● Pad green	Monomatic I / LS Watertank Twinvac / Duovac	  
3	 scrubber drying two-step	<input type="checkbox"/>	Antiwax forte classic 30 - 50% G Rewit 2000 10 - 20% B Relino 20 - 50%		⊙ Scrubbing brush Filament V ⊙ Scrubbing brush Tynex B ● Pad green	Duo- / Discomatic Drivematic / Robomatic	large areas   
4	 rinsing	<input type="checkbox"/>	pure water	100%	S ⊙ Microsol fibre pad ⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon	Monomatic I / LS Watertank Twinvac / Duovac	pH 7 
4	 rinsing	<input type="checkbox"/>	pure water	100%	S ⊙ Microsol fibre pad ⊙ Scrubbing brush Filament ⊙ Scrubbing brush Supernylon	Duo- / Discomatic Drivematic / Robomatic	large areas pH 7 
5	 wet mopping single step	<input type="checkbox"/>	Biosan	3%	Silksmooth-mop Microbrush-mop Micro woven-1	Wetbox system Wetcar / Drewell Variwet Plus	if needed, bad smell could be removed with  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

important: change pad often.

General instructions for cleaning and care













no 40  **Cement surface layer (rough)**



protective treatment

object _____ date _____
 address _____ customer _____
 room classification _____ representative _____

work process: select one work stage from each number

↓ cleaning method		recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments
1	 dry vacuum cleaning			F S Dust roller nozzle F Combi-nozzle	Monovac Portavac Twinvac	
1	 dusting damp mopping			S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	if needed
pore filling (only if necessary)						
2	 pore filling	F Porosol	100%	Cover for Florfix Florfix-mop Multi squeegee	Florfix Balit with velcro	If necessary, one layer on porous surface.  
coating						
3	 coating	Stoner Mepol HM	100% 100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	1 - 3 thin layers  
4	 dusting damp mopping			Masslinn 2000 B S Microsol cloth B S Synthetic fur	Balit with pad sole Balit with velcro	if needed
coating						
2	 impregnation	F Imprasol	100%	Cover for Florfix Florfix-mop	Florfix Balit with velcro	apply first layer with care.  

* basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / H: handball resin / P: polishing / S: structured / V: heavily soiled

important: if needed

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

do not coat impregnated floors.

Process treatment of protection: see description of method.

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

General instructions for cleaning and care



no 40 Cement surface layer (rough)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.com.

Wear the required personal protective equipment (PPE): e.g. protective gloves, safety goggles, work shoes.

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.com.

The recommended colours of pad and brushes consist to the actual wWetrok product range.

Follow the special cleaning and care instructions of the floor manufacturer.

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Do not coat structured floor coverings.

Strong acids and abrasive pads and brushes can destroy limestone and cement-bonded artificial stone.

Cement floors are sensitive to strong acids and strongly alkaline cleaners.

Do not use maintenance and protection products in wet areas. Danger of slipping!



Cement mortar consists of Portland cement and sand.

Cement coatings are painted with special concrete paints and treated with concrete sealants.

Distinguishing feature: cement-bound synthetic stone acid assay: apply a little basic sanitary cleaner to the magnesite covering. Foams up: material damage!



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.